



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7204HUHI-M1/S(C) 4 CHANNELS ACUSENSE Hikvision	EXTENDER ETHERNET VIA UTP CABLE EA-EOU101 COP
		
	224.87 EUR 224.87 EUR	77.86 EUR 77.86 EUR
LAN ports	...	1 pcs RJ45
Transmission ports	...	1 pcs BNC + BNC / UTP converter - cable terminals
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Transmission speed	...	10 / 100 Mbps Full Duplex
Transmission range	...	max. 1000 m
Main features	...	<ul style="list-style-type: none"> • Plug & Play • The device uses 1 pair of twisted-pair cable for transmission to 1 IP camera
Video inputs	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Video outputs	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket	...
Audio inputs	1 pcs CINCH, Coaxial audio - Audio from cameras	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265+ / H.265 / H.264 / H.264+	...

Image records resolutions	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 2,3,4 CH only , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8 Mpx - 3840 x 2160 	...
Recording speed adjustment	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 8M-N @ 1 ... 15 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
Supported hard drives	1 x 10 TB SATA	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time	...
Network interface	1 x RJ-45 - 10/100 Base-TX	...
Bitrate	32 ... 10240 kbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	DHCP or 192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	554 RTSP, 8000	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream 	...
Alarm inputs / outputs	—	...
PTZ control	<ul style="list-style-type: none"> • Control compatible with coax HD-TVI Hikvision • RS-485 - PELCO-D/P 	...
Motion Detection	2.0	...
USB	2 x USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...
Main features	<ul style="list-style-type: none"> • DVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles 	...
Power supply	12 V DC / 1.5 A (power adapter included)	12 V DC / 500 mA (power adapter included)
Color	Black	...
Weight	1.1 kg	0.14 kg
Dimensions	315 x 250 x 45 mm	120 x 33 x 33 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	COP
SAP Code	300226972	...
Guarantee	3 years	2 years

