



	<a href="#">LED LIGHTING CONTROLLER LED-RGBW-WC/RF 2.4 GHz, RGBCCT (RGBWW) 12 ... 24 V DC MiBOXER / Mi-Light</a>	<a href="#">LAMINATED PVC CARD ATLO-100</a>
		
	11.96 EUR 11.96 EUR	0.17 EUR 0.17 EUR
Standard	...	—
Application	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips	...
Rated voltage	12 ... 24 V DC	...
Maximal total load	• 144 W @ 12 V, • 288 W @ 24 V	...
Total maximal current	6 A / Channel, 12 A (total)	...
Number of inputs	1	...
Number of outputs	5 (power)	...
Connector type	• screw terminals, • 5.5/2.1 socket / screw terminals - power input	...
Wireless	2.4 GHz	...
Radio communication range (at open area)	30 m	...
Mobile phones support	—	...
Main features	The repeater function allows you to transfer control to subsequent LED-W-WC / LED-RGB-WC / LED- RGBW-WC modules even beyond the direct range of the remote control	...
Housing	Plastic	...
Color	White	...
Operation temp	-10 °C ... 40 °C	...
Weight	0.03 kg	0.006 kg
Dimensions	75 x 36 x 17 mm	86 x 54 x 1 mm
Manufacturer / Brand	MiBOXER / Mi-Light	ATLO
Guarantee	2 years	2 years