




	ELECTRIC CABLE YKY-5X6.0	IP SPEED DOME CAMERA OUTDOOR SD1A404XB-GNR - 3.7 Mpx 2.8 ... 12 mm DAHUA	GRAPHITE VARNISH GRAPHITE-VARNISH 2 X VIAL 1.5 ml AG TERMOPASTY
			
	4.65 GBP 4.65 GBP	431.96 GBP 431.96 GBP	2.43 GBP 2.43 GBP
Standard	...	TCP/IP	...
Sensor	...	1/2.8 " STARVIS™ CMOS	...
Package	2 x Vial 1.5 ml (varnish + solvent)
Matrix size	...	4 Mpx	...
In section	100 m . Price for 1m when buying a whole roll
Application	<ul style="list-style-type: none"> • Repair and renovation of graphite coatings in electronic devices, • Reconstruction of paths in printed circuit boards
Inner conductor	5 x 6.0 mm ² - Cu wire
Rated voltage	0.6 / 1 kV
Outer coating	Ø 17.2 mm - PVC
Coating color	Black
Main features	<ul style="list-style-type: none"> • Density : 1.2 g/cm³ @ 20 °C, • Viscosity : 15 ... 50 Pa·s @ 20 °C • Good electrochemical corrosion protection on metal • Photosensitive varnish • Dedicated solvent (ethyl acetate) included
Resolution	...	2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	...	2.8 ... 12 mm	...
View angle	...	<ul style="list-style-type: none"> • 97 ° ... 31.6 ° (manufacturer data) • 90 ° ... 43 ° (our tests result) 	...
Optical zoom	...	x 4	...
Digital zoom	...	— x 16	...
Range of IR illumination	...	15 m	...
Video output	...	—	...
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 70 °/s (horizontal) • 0.1 °/s ... 30 °/s (vertical) 	...
Preset rotation speed	...	<ul style="list-style-type: none"> • 80 °/s (horizontal) • 40 °/s (vertical) 	...
Horizontal rotation range	...	0 ° ... 355 ° - Rotation of the head is limited by stops	...
Vertical rotation range	...	5 ° ... 90 °	...
RS-485 interface	...	—	...
Number of presets	...	300	...
Horizontal scan	...	✓	...
Route settings	...	8	...
Image compression method	...	H.265 / H.265+ / H.264 / H.264+ / MJPEG	...
Alarm inputs / outputs	...	—	...
Main stream frame rate	...	25 fps - 4 Mpx	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP RTCP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, ARP	...
WEB Server	...	Built-in, NVR compliance	...
Max. number of on-line users	...	20	...
ONVIF	...	20.06	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • External microphone input, • Audio output, • Bi-directional audio streaming support • Audio detection 	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Default IP address	...	192.168.1.108	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EIS - Electronic Image Stabilization • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles, abandoned/missing object, video tampering, scene changing, face detection, people counting 	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 710 mA 	...
Power consumption	...	≤ 8.5 W	...
Housing	...	Speed Dome Metal, Plastic	...
Color	...	Black + White	Black
"Index of Protection"	...	IP66	...
Vandal-proof	...	IK08	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	...	0.51 kg	...
Dimensions	...	Ø 128 x 65 mm	...
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	...	DAHUA	AG TERMOPASTY
Guarantee	2 years	5 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00