

	CAMERA CORNER BRACKET DS-1276ZJ Hikvision	IP CAMERA IPC-HFW2849S-S-IL-0280B WizSense - 8.3 Mpx 4K UHD 2.8 mm DAHUA
		
	361.31 NOK 361.31 NOK	3485.27 NOK 3485.27 NOK
Standard	...	TCP/IP
Suitable for cameras	Hikvision	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Material	Metal	...
Matrix size	...	8.3 Mpx 4K UHD
SAP Code	302700379	...
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2880 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Scanning system	...	Progressive
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 104 ° (our tests result)
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
Min. illumination	...	0.008 Lux / F1.6 (color)
S/N ratio	...	> 56 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio detection • Compliance with the AAC standard
Main stream frame rate	...	20 fps @ 8.3 Mpx 25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
WEB Server	...	Built-in
Max. number of on-line users	...	20
ONVIF	...	21.12

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support • SMD PLUS - searching for an object classified as: human, motor vehicle • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles video tampering
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 5 W @ 12 V DC • ≤ 5.9 W @ PoE
Housing	...	Compact - Metal
Color	White	White + Black
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	1.85 kg	0.47 kg
Dimensions	108 x 175 x 250 mm	166 x 70 x 70 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	Hikvision	DAHUA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00