

	IP CAMERA IPC2125LE-ADF28KM-G - 5 Mpx 2.8 mm UNIVIEW	IP CAMERA TC-C35WQ SPEC:I5W/E/Y/2.8MM/V4.2 - 5 Mpx 2.8 TIANDY	POWER SUPPLY ADAPTER 12V/1.5A/PROTEC
			
	180.10 EUR 180.10 EUR	254.78 EUR 254.78 EUR	4.54 EUR 4.54 EUR
Standard	TCP/IP	IP	...
Adapter type	Switching
Power voltage	230 V AC
Matrix size	5 Mpx
Output voltage	12 V DC
Maximal load	1.5 A
Output power	18 W
Average active efficiency	85.3 %
Power consumption at no-load	< 0.1 W
Protections	<ul style="list-style-type: none"> • Overload • Short-circuit
Number of outputs	1 pcs
Power connectors type	2.1/5.5 mm - Straight plug
Housing type	Plastic
Main features	Splash-proof casing
Operation temp	-30 °C ... 40 °C
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	...
S/N ratio	> 52 dB
Lens	2.8 mm	2.8	...
RS-485 interface	—
View angle	<ul style="list-style-type: none"> • 113 ° (manufacturer data) • 104 ° (our tests result) 	104 °	...
Range of IR illumination	50 m	50 m	...
White light LED illuminator range	...	15 m	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD card support up to 512GB	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	S+265 / H.265 / H.264	...
Alarm inputs / outputs	—	1 / 1	...
Network interface	10/100 Base-T (RJ-45)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection 	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Audio input • Audio output • Bi-directional audio streaming support • Audio transmission via network 	...
Main stream frame rate	25 fps @ 5 Mpx	<ul style="list-style-type: none"> • 25 fps @ 5 Mpx • 50 fps @ 2 Mpx 	...
Interface	...	10/100 Base-TX (RJ-45)	...
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	Built-in	Built-in	...
Intelligent image analysis	...	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • video tampering 	...
Max. number of on-line users	32	2	...
ONVIF	✓	✓	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus 	...
Default IP address	DHCP or 192.168.1.13	192.168.1.2	...
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 554	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	3000, 3001	...
Mobile client access ports	80	3000, 3001	...
Port ONVIF	80	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Mechanical protection class	...	—	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • Early Warning (EW) - combination of white light warning with audio signals • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Audio detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA 	...
Power consumption	≤ 6 W	≤ 8 W	...
Housing	Compact, Metal + Plastic	Compact - Metal	...
Color	White	White	...
"Index of Protection"	IP67	IP67	IP53
Vandal-proof	—
Operation temp	-30 °C ... 60 °C	-40 °C ... 65 °C	...
Weight	0.45 kg	0.52 kg	0.17 kg
Dimensions	190 73 x 71 mm	170 x 71 x 71 mm	130 x 80 x 38 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian	...

Manufacturer / Brand	UNIVIEW	TIANDY	...
Guarantee	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00