



	INFRA-RED BARRIERS SATEL ACTIVA-7 7 BEAMS SATEL	IP CAMERA APTI-AI203PV21-28W - 1080p 2.8 mm
		
	255.47 USD 255.47 USD	31.95 USD 31.95 USD
Number of beams	7	...
Standard	...	TCP/IP
Detection method	Programmable number of beams, which interruption trigger an alarm	...
Sensor	...	1/2.9 " Progressive Scan CMOS
Outdoor detection range	10 m	...
Matrix size	...	2.1 Mpx
Indoor detection range	20 m	...
Beam characteristics	Transmission encoding	...
Interruption time (blocking of the beam)	40 ... 1000 ms	...
Alarm period	2 s	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 720 - 720p
Tamper contact	NC	...
Lens	...	2.8 mm
Assembly	Possibility to mount to the wall	...
View angle	...	105 °
Range of IR illumination	...	30 m
Current consumption	max. 45 mA	...
Angles adjustment range	—	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Operation temp. / Relative humidity	-25 °C ... 55 °C / max. 95 %	...
Audio	...	—
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in - port 80
Transmitter or receiver dimensions	1842 x 25 x 26 mm	...
Max. number of on-line users	...	10
Transmitter and receiver weight	0.872 kg	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	...	✓
Main features	<ul style="list-style-type: none"> • trimmer sensitivity adjustment • RS-232 port allows to programming using the PC with ACTIVA software installed 	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • RESET button - on the cable • Sharpness - sharper image outlines
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply	12 V DC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 220 mA

Power consumption	...	≤ 2.7 W
Housing	...	Dome, Metal + Plastic
Vandal-proof	...	—
Color	Black + Silver	White
"Index of Protection"	IP44	IP65
Operation temp	...	-20 °C ... 60 °C
Weight	...	0.23 kg
Dimensions	...	Ø 108 x 83 mm
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, Portuguese, Russian, Turkish
Manufacturer / Brand	SATEL	APTI
Guarantee	2 years	2 years