





	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	REMOTE CONTROL FOR LED LIGHTING CONTROLLERS FUT092 2.4 GHz, MONO, CCT, RGB, RGBW, RGB CCT (RGBWW) MiBOXER / Mi-Light	CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P/RGB 10 mm ORNO	CONNECTOR FOR LED STRIPS UQS-COB-12W-SS 10 mm
				
	95.36 EUR 95.36 EUR	9.73 EUR 9.73 EUR	0.98 EUR 0.98 EUR	0.64 EUR 0.64 EUR
Sensor	SmartSens CMOS - 2 Mpx
Number of power outputs	1 pcs	...
Application	...	Works with LED lighting : (RGB/RGBW/RGB CCT/CCT/MONO) 12-24V LED strips	Works with LED lighting RGB	Works with LED lighting - COB LED strips
Number of channels	...	4
Strip width	10 mm	10 mm
Resolution	1920 x 1080 px - 1080p
Length of the cable	140 mm	...
Wireless	...	2.4 GHz
Radio communication range (at open area)	...	30 m
Lens	2.0 mm F1.2
Main features	...	Touch control keys
View angle	140 °
Maximal power voltage	48 V	...
IR illuminator	5 ... 10 m
LED illuminator	—
proximity reader built-in	Unique EM 125kHz
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Network interface	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Manufacturer / Brand	...	MiBOXER / Mi-Light	ORNO	MW Lighting
Image compression method	H.265 / H.264
Supported audio formats	G.711

Main features	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance
Mount	Surface-mounted
Power supply	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af) 	2 x 1.5V, type AAA/LR03 battery (not included)
Housing	Aluminum + Plastic (ABS)	Plastic	Plastic	Plastic
Color	Silver	White	White	Transparent
"Index of Protection"	IP44	...	—	—
Operation temp	-20 °C ... 55 °C	-20 °C ... 60 °C
Weight	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	0.07 kg (without battery)	0.002 kg	0.002 kg
Dimensions	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	137 x 55 x 21 mm	140 x 15 x 5 mm	12 x 10 x 5 mm
Guarantee	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00