

	TV OR MONITOR MOUNT MC-711N MACLEAN	SWITCH POE GTX- CLM1-6-4G2G 4-PORT	SMART SWITCH SWITCHBOX-DIN/BLEBOX Wi-Fi, 230 V AC	ROUTER RUT140 Wi-Fi 2.4 GHz 300 Mbps Teltonika	DOUBLE SOCKET OUTLET DGZ2MZ.01/11-SIMON54 250 V 16 A	INDUSTRIAL SWITCH TSF010 5-PORT Teltonika
						
	169.13 NOK 169.13 NOK	783.66 NOK 783.66 NOK	543.83 NOK 543.83 NOK	613.77 NOK 613.77 NOK	72.99 NOK 72.99 NOK	349.01 NOK 349.01 NOK
Frequency range	2.4 GHz
Rated voltage	230 V AC	...	250 V AC	...
Antenna type	SMA-RP socket - without antenna
Maximal current load	16 A	...
Maximal total load	3680 W (resistance load) / 500 W (inductive or capacitive load)
Standards	IEEE 802.11 b/g/n
Grounding	✓	...
Total maximal current	16 A
Number of inputs	2
Cable terminals	screw terminals	...
Number of outputs	1
Socket type	2 x CEE 7/5	...
Connector type	screw terminals
Protection shutter	✓	...
Management	...	✓	—
Mounting standard	VESA : 75, 100, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
Application	switching devices on/off	...	Flush-mounted, Simon 54 product series, for Premium frames	...
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Assembly	Claw or screw mounting	...
Screen size range	26 " ... 55 "
Transmission speed	...	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE	10 / 100 Mbps - 5 LAN ports
MAC addresses table	2k
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS
LAN ports	...	• 4 x RJ45 (4 x PoE (802.3af/at)), • 2 x RJ45 - Uplink	...	1 x 10 / 100 Mbps	...	5 x RJ45
Bearing capacity	30 kg
WAN interface	1 x 10 / 100 Mbps
Distance from mounting surface	63 ... 415 mm
Default admin user / password	...	admin / admin
Tilt adjustment	-15 ° ... 10 °
Maximal output power	...	30 W / port PoE
Maximal total power	...	65 W
LED indicators	Power, WAN, LAN
Horizontal rotation	-90 ° ... 90 °
Rotation in the plane of the screen	± 3 °
LTE	—
QSS	—
WDS	—
DHCP server	✓
DDNS	Support > 25
Operation modes	...	• EXTEND mode • Port Isolation	...	Access Point, Station
LED diodes	...	PWR, PoE, Link/Act	Power, Link/Act
"Index of Protection"	IP20	...	IP20	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Color	Black	...	White	...	White (RAL 9003)	...
Housing	...	Metal	Plastic (ABS), DIN, TS-35 rail mounting	...	Non-halogen plastic, PC	Aluminum
Protections	...	Overvoltage ± 4 kV	...	<ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA-PSK/WPA2-PSK • WPA-EAP • WPA3-SAE • WPA3-EAP • OWE • AES-CCMP • TKIP • WEP • EAP-TLS • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering • Firewall • Support DDOS, SYN, SSH, HTTP/HTTPS defence • White list / Black list 	...	<ul style="list-style-type: none"> • Overvoltage min. 64.4 V / max. 71.2 V • Overvoltage max. 60 V • Reverse polarity of the input voltage max. 80 V
Management interface	Web browser, Teltonika RMS application
Default IP address	...	192.168.2.1	...	192.168.1.1
Operating system	RutOS (Linux OS based)
Firmware update	✓
Main features	...	<ul style="list-style-type: none"> • QoS - mechanisms, which provide the high quality of transmission • Spanning Tree STP/RSTP • VLAN support - Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • Port mirroring function • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • sunrise and sunset mode, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • Energy consumption metering, • Power measurement, • Charts and measurement history • µWiFi technology support • Illuminated, color front panel with an additional control button 	<ul style="list-style-type: none"> • Support for Mesh technology, • Compliance with the Modbus, DLMS, DNP3, OPC UA protocol • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Static / dynamic routing • Support for VoIP technology, • View topology and network status • WMM support (QoS mechanism of the 802.11e standard) • DHCP Relay support • Load balance • Ability to work as a Hotspot, • VLAN support • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Compliance with the MQTT protocol • SNMP v1/v2/v3/Trap • Support for IoT (Internet of Things) systems, • Configuration using the Teltonika RMS application • RESET button • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 3-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Light and durable construction - Aluminum, • Flat housing profile, • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 3-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 	
Certificates	...	CE, FCC, RoHS	...	CE, UKCA, FCC, WEEE	...	CE, UKCA, FCC
Power supply	...	100 ... 264 V AC, Power adapter included	...	<ul style="list-style-type: none"> • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 	...	7 ... 57 V DC (power adapter not included)
Power consumption	≤ 2 W	...	≤ 1.5 W
Operation temp	...	-10 °C ... 45 °C	-20 °C ... 50 °C	-40 °C ... 75 °C	...	-40 °C ... 75 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	2.93 kg	0.65 kg	0.07 kg	0.15 kg	0.078 kg	0.15 kg
Dimensions	455 x 420 x (63 ... 415) mm	200 x 118 x 44 mm	90 x 17.5 x 65 mm	123 x 69 x 25 mm	<ul style="list-style-type: none"> • 81 x 75 x 46 mm • 20 mm - mounting depth 	121 x 28 x 50 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	MACLEAN	...	BleBox	Teltonika	KONTAKT Simon	Teltonika
Guarantee	2 years	2 years	2 years	2 years	6 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00