




	METER OF CAPACITANCE, INDUCTANCE AND RESISTANCE UT-603	ELECTRIC CABLE YKY-3X2.5/200	CLEANER FOR RECOVERY OF POTENTIOMETERS KONTAKT-PR/400 SPRAY 400 ml AG TERMOPASTY
			
	54.40 EUR 54.40 EUR	1.64 EUR 1.64 EUR	6.53 EUR 6.53 EUR
DC voltage measurement	—
AC voltage measurement	—
Package	Spray 400 ml
DC current measurement	—
Application	Cleaning and regeneration of potentiometers
In section	...	200 m . Price for 1m when buying a whole roll	...
AC current measurement	—
Inner conductor	...	3 x 2.5 mm ² - Cu wire	...
Rated voltage	...	0.6 / 1 kV	...
Outer coating	...	Ø 10 mm - PVC	...
Coating color	...	Black	...
Resistance measurement	200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 0.001 kΩ , 20 kΩ ± (0.8% + 1) @ 0.01 kΩ , 200 kΩ ± (0.8% + 1) @ 0.1 kΩ , 2 MΩ ± (0.8% + 1) @ 0.001 MΩ , 20 MΩ ± (2.0%(RD-12) + 5) @ 0.01 MΩ 2000 MΩ @ 1 MΩ - visual measurement

Capacitance measurement	2 nF ± (1% + 5) @ 0.001 nF , 20 nF ± (1% + 5) @ 0.01 nF , 200 nF ± (1% + 5) @ 0.1 nF , 2 µF ± (4% + 5) @ 0.001 µF ... , 20 µF ± (4% + 5) @ 0.01 µF , 200 µF ± (4% + 5) @ 0.1 µF , 600 µF @ 1 µF - visual measurement
Inductance measurement	2 mH ± (2% + 8) @ 0.001 mH , 20 mH ± (2% + 8) @ 0.01 mH , 200 mH ± (2% + 8) @ 0.1 mH , 2 H ± (5% + 5) @ 0.001 H , 20 H ± (5% + 5) @ 0.01 H , 200 H @ 0.1 H - visual measurement
Frequency measurement	—
Square-wave signal duty ratio measurement	—
Temperature measurement	—
hFE	✓
Diode test	✓
Sound signal of the continuity test	✓
Checking TTL logic states	—
RS-232	—
Main features	<ul style="list-style-type: none"> • Large, readable LCD display with backlight • Hold - stopping the meter reading • Aesthetic and solid construction 	...	Spray preparation with a brush for easy application in hard-to-reach places
Power supply	9V, type 6LR61 battery - included
Weight	0.29 kg	...	0.36 kg
Dimensions	172 x 84 x 41 mm	...	Ø 66 x 187 mm
Manufacturer / Brand	UNI-T	...	AG TERMOPASTY
Guarantee	2 years	2 years	...