



	<a href="#">WIRELESS VIDEO DOORPHONE ATLO-DBC51-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">INDICATOR MODULE VTO4202F-ML DAHUA</a>	<a href="#">ROUTER ARCHER-C80 2.4 GHz, 5 GHz 600 Mbps + 1300 Mbps TP-LINK</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LPA68-221</a>
				
	91.35 EUR 91.35 EUR	40.34 EUR 40.34 EUR	48.57 EUR 48.57 EUR	7.18 EUR 7.18 EUR
Frequency range	...	...	2.4 GHz, 5 GHz	...
Sensor	SmartSens CMOS - 2 Mpx	...	...	...
Antenna type	...	...	4 x Omnidirectional antenna	...
Resolution	1920 x 1080 px - 1080p	...	...	...
Mounting standard	...	...	...	VESA : 100, 200, 200x100
Lens	2.0 mm F1.2	...	...	...
Screen size range	...	...	...	23 " ... 43 "
View angle	140 °	...	...	...
Bearing capacity	...	...	...	30 kg
Standards	...	...	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac @ 5 GHz	...
IK rating	...	IK07	...	...
Distance from mounting surface	...	...	...	56 ... 204 mm
Baud rates	...	...	600 Mbps + 1300 Mbps	...
Tilt adjustment	...	...	...	-8 ° ... 5 °
IR illuminator	5 ... 10 m	...	...	...
LED illuminator	—	...	...	...
Horizontal rotation	...	...	...	-90 ° ... 90 °
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...	...	...
Rotation in the plane of the screen	...	...	...	—
LAN ports	...	...	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	...
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n	...	...	...
Network interface	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi	...	...	...
LED indicators	...	...	Power, 2.4 GHz WLAN, 5 GHz WLAN, LAN, WAN	...
Mobile phones support	The <a href="#">Tuya Smart</a> free application on Android The <a href="#">Tuya Smart</a> free application on iOS	...	...	...
Image compression method	H.265 / H.264	...	...	...
Supported audio formats	G.711	...	...	...

Receiver sensitivity	...	...	2.4 GHz : <ul style="list-style-type: none"> <li>• 11g 6M : -97 dBm</li> <li>• 11a 54M : -77 dBm</li> <li>• 11n VHT20_MCS0 : -97 dBm</li> <li>• 11n VHT20_MCS8 : -72 dBm</li> <li>• 11n VHT40_MCS0 : -92 dBm</li> <li>• 11n VHT40_MCS9 : -67 dBm</li> </ul> 5 GHz : <ul style="list-style-type: none"> <li>• 11a 6M : -98 dBm</li> <li>• 11a 54M : -78 dBm</li> <li>• 11ac VHT20_MCS0 : -98 dBm</li> <li>• 11ac VHT20_MCS8 : -72 dBm</li> <li>• 11ac VHT40_MCS0 : -92 dBm</li> <li>• 11ac VHT40_MCS9 : -68 dBm</li> <li>• 11ac VHT80_MCS0 : -89 dBm</li> <li>• 11ac VHT80_MCS9 : -64 dBm</li> </ul>	...
DDNS	...	...	✓	...
DHCP server	...	...	✓	...
Firmware update	...	...	✓	...



Main features	<ul style="list-style-type: none"> <li>• Micro SD memory cards up to 256GB support (possible local recording)</li> <li>• Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording,</li> <li>• Motion Detection,</li> <li>• PIR detector,</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode,</li> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bidirectional communication,</li> <li>• Noise and echo reduction</li> <li>• Full support via network</li> <li>• 5 on-line users,</li> <li>• Possibility to work in cloud - you don't need to redirect the ports,</li> <li>• Video PUSH personal messaging - Motion Detection,</li> <li>• Video recording - Motion Detection, Doorbell button,</li> <li>• Automatic events notification via Email messages</li> <li>• Lock control - Relay output</li> <li>• Tamper protections</li> <li>• Google Home, Amazon Echo compliance</li> </ul>	...	...	...
Mount	Surface-mounted	...	...	...
Protections	...	...	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding	...
Management interface	...	...	Web browser, TP-LINK Tether	...
Transmitter power	...	...	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz	...
Housing	Aluminum + Plastic (ABS)	Metal + Plastic	...	...
Color	Silver	Silver	...	Black
Power supply	<ul style="list-style-type: none"> <li>• 12 V DC / 1 A (power adapter included)</li> <li>• 48 V PoE (802.3af)</li> </ul>	5 V DC - Supplied from other modules	12 V DC / 2 A (power adapter included)	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP44	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• TP-Link OneMesh™ support,</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• Airtime Fairness - technology that improves network performance when multiple clients with different data rates appear in it</li> <li>• Firewall</li> <li>• Internet access filtering</li> <li>• Static / dynamic routing</li> <li>• Built-in 4-port switch</li> <li>• Access Point</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• QoS</li> <li>• Access control</li> <li>• Remote management</li> <li>• DMZ</li> <li>• UPnP</li> <li>• Port forwarding</li> <li>• parental control</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• DHCP client list</li> <li>• VPN networks: Open VPN, PPTP VPN</li> <li>• SSID hiding</li> <li>• IPv6 compliance</li> <li>• Smooth transmission in HD quality - IGMP Proxy/Snooping, VLAN, Tag</li> </ul> VLAN functions contribute to optimal IPTV transmission	...
Operation temp	-20 °C ... 55 °C	...	0 °C ... 40 °C	...
Permissible relative humidity	...	...	10 % ... 90 % (non-condensing)	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Weight	<ul style="list-style-type: none"> <li>• 0.212 kg - Wireless Video Doorbell</li> <li>• 0.046 kg - rain cover</li> </ul>	0.12 kg	0.31 kg	1.03 kg
Dimensions	<ul style="list-style-type: none"> <li>• 141 x 87 x 25 mm - Wireless Video Doorbell</li> <li>• 147 x 94 x 40 mm - rain cover</li> </ul>	100 x 50 x 29 mm	215 x 117 x 32 mm	230 x 230 x (56 ... 205) mm
Manufacturer / Brand	...	DAHUA	TP-LINK	BRATECK
Guarantee	2 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00