



	CURRENT TRANSFORMER SC-16 ZAMEL	IP CAMERA DS-2CD1027G2H-LIU(2.8MM) ColorVu - 1080p Hikvision
		
	12.59 GBP 12.59 GBP	149.24 GBP 149.24 GBP
Support	MEW-01	...
Standard	...	IP
Maximum continuous primary current	100 A	...
Gear	3000 : 1	...
Frequency range	50/60 Hz	...
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p
Operation temp	-15 °C ... 60 °C	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Wire gauge	16 mm (max)	...
Lens	...	2.8 mm
Main features	Openable core	...
View angle	...	115 °
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network
Main stream frame rate	...	20 fps @ 1080p
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓

Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 450 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE • ≤ 5.4 W @ 12 V DC
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.09 kg	0.29 kg
Dimensions	45 x 34 x 31	173 x 70 x 68 mm
Supported languages	...	Polish, Ukrainian
Manufacturer / Brand	ZAMEL	Hikvision
SAP Code	...	311325408

Guarantee	2 years	3 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00