





	HUB USB 3.0 CT2U3-13AB-EU-WH-BP 1 m	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1801T-IL-A-0280B-S2 - 8.3 Mpx 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE57H0T-VPITF(2.8mm)(C) - 5 Mpx Hikvision	RELAY MODULE ESP12-2R-D8 Wi-Fi
				
	59.47 AUD 59.47 AUD	239.68 AUD 239.68 AUD	141.93 AUD 141.93 AUD	18.14 AUD 18.14 AUD
PTZ control	Wi-Fi
Standard	...	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / CVBS	...
Protocol	IEEE 802.11 b/g/n/e/i, Wi-Fi Direct (P2P), TCP, UDP
Sensor	...	Progressive Scan CMOS	Progressive Scan CMOS	...
Connectors	<ul style="list-style-type: none"> • 1 x Socket - USB-B 3.0 • 13 x socket - USB-A • 1 x Power socket - 5.5/2.1 socket
Matrix size	...	8.3 Mpx	5 Mpx	...
Number of inputs	—
Length of the cable	1 m
Number of relay outputs	2 pcs
USB standard	3.0
Relay maximal load	10 A / 250 V AC , 10 A / 30 V DC
Output	2 x NO/NC
Main features	<ul style="list-style-type: none"> • Solid workmanship • LED indication • Each socket has a separate switch 	<ul style="list-style-type: none"> • LED indication • Programming with Arduino IDE or Eclipse tools • The module can be used as an element of IoT (Internet of Things) systems • The Wi-Fi module works in the 2.4 GHz band
IR illuminator support	ICR - Movable InfraRed filter	...
Resolution	...	3840 x 2160 - 8.3 Mpx @ HD-CVI @ 25 fps , 3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 25 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL 	...
Lens	...	2.8 mm	2.8 mm	...
View angle	...	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 101 ° (our tests result) 	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 79 ° (our tests result) 	...
Range of IR illumination	...	30 m	20 m	...
White light LED illuminator range	...	30 m
IR illuminator power adjustment	...	Automatic	Automatic	...

Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu	...	✓	✓	...
SAP Code	300613629	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • D-WDR - Wide Dynamic Range • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	12 V DC / 5 A (included)	12 V DC / 480 mA	12 V DC / 340 mA	7 V ... 30 V DC or 5 V DC (power adapter not included)
Power consumption	...	≤ 5.7 W	≤ 4.3 W	...
Housing	Plastic	Dome, Metal	Dome, Metal	...
Color	...	White	White	...
"Index of Protection"	...	IP67	IP67	...
Vandal-proof	...	—	IK10	...
Operation temp	...	-40 °C ... 60 °C	-40 °C ... 60 °C	...
Weight	0.191 kg	0.48 kg	0.37 kg	0.04 kg
Dimensions	235 x 62 x 28 mm	Ø 106 x 99 mm	Ø 111 x 85 mm	78 x 47 x 19 mm
Manufacturer / Brand	ORICO	DAHUA	Hikvision	...
Guarantee	2 years	3 years	3 years	2 years