






	INDUSTRIAL POE SWITCH PFS3220-16GT-240-V2 16-PORT SFP DAHUA	MOUNTING CUBE FOR EMERGENCY BUTTON APWK/KOSTKA	POWER DISTRIBUTION UNIT AK-SP-05B AKYGA	RFID PROXIMITY CARD ATLO-114*P10	UNIVERSAL CLEANING WIPES UNI-WIPES/24 AG TERMOPASTY
					
	427.26 AUD 427.26 AUD	6.53 AUD 6.53 AUD	14.37 AUD 14.37 AUD	8.15 AUD 8.15 AUD	1.56 AUD 1.56 AUD
Application	Wet wipes for the care of office equipment
Connectors type	...	4 x screw terminals
Rated voltage	230 V AC / 50 Hz
Number of terminal pairs	...	4
Total maximal current	10 A
Wipe dimensions	220 x 160 mm
Maximal total load	2500 W
Packaging	24 wipes
In package	10 pcs The price for package	...
Response time	< 25 ns
Standard	Unique EM 125kHz	...
Number of outlets	5 grounded outlets 10A/250V
Compatibility	EM4100/4102	...
Possibility of programming the serial number (ID)	—	...
Automatic delayed fuse	10 A / 250 V
Ability to write to internal memory	—	...
Serial Number overprint	—	...
Nominal voltage of surge suppressor	250 V / 50 Hz
DC filter to eliminate interferences	RFI ≤ 10 dB
Maximum stroke current	4.5 kA
Maximum energy absorption	150 J
Switch	with light indication
Length of the cable	3.0 m
Housing	Plastic (ABS)
Color	...	Green	Black
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 (2 Hi-PoE (802.3bt) + 14 PoE (802.3af/at) - 10/100/1000 Base-T), • 2 x Uplink (RJ45 - 10/100/1000 Base-T), • 2 x Uplink (port SFP - 1000 Base-X)
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 16 x LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 x Uplink ports, • 1000 Mbps - 2 x SFP ports
Management	—
Maximal output power	<ul style="list-style-type: none"> • 30 W / port PoE • 90 W / port Hi-PoE
Maximal total power	240 W
MAC addresses table	8k

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	protection against lightning discharges and voltage differences and strokes between devices	<ul style="list-style-type: none"> • Range : ~ 15 cm • The TK-4100 chip 	...
LED diodes	Power, Link/Act, PoE, System
Certificates	CE
Power supply	100 ... 240 V AC
Operation temp	-10 °C ... 55 °C	...	5 °C ... 50 °C
Weight	3.3 kg	0.008 kg	0.372 kg	0.006 kg	...
Dimensions	440 x 300 x 44 mm	21 x 19 x 16 mm	305 x 50 x 40 mm	85 x 54 x 2 mm	...
Manufacturer / Brand	DAHUA	...	AKYGA	ATLO	AG TERMOPASTY
Guarantee	5 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00