




	<a href="#">HD-CVI, PAL CAMERA DH-HAC-HFW2221SP-028 0B - 1080p 2.8 mm DAHUA</a>	<a href="#">SMART SWITCH ATLO-B1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">PATCHCORD RJ45/10-GREY 10 m</a>
			
	336.00 PLN 336.00 PLN	21.61 PLN 21.61 PLN	9.46 PLN 9.46 PLN
Application	...	switching devices on/off	...
Standard	HD-CVI, PAL	...	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...
Matrix size	2.1 Mpx	...	...
Maximal total load	...	2400 W	...
Total maximal current	...	10 A	...
Cable	...	...	UTP cat. 5e : RJ-45 Plug / RJ-45 Plug
Number of inputs	...	1	...
Number of outputs	...	1	...
Length of the cable	...	...	10 m
Connector type	...	screw terminals	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p 960 x 576 - 960H, PAL	...	...
Lens	2.8 mm	...	...
Mobile phones support	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...
View angle	<ul style="list-style-type: none"> <li>• 116 ° (manufacturer data)</li> <li>• 111 ° (our tests result)</li> </ul>	...	...
S/N ratio	> 65 dB	...	...
Range of IR illumination	30 m	...	...
IR illuminator power adjustment	Automatic	...	...
IR illuminator support	ICR - Movable InfraRed filter	...	...
Main features	...	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure</li> <li>• Pairing button</li> <li>• Wi-Fi indicator</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>

Video output	HD-CVI / PAL - 1 Vpp / 75 Ω	...	...
Operation temp	...	-20 °C ... 50 °C	...
Permissible relative humidity	...	≤ 80 %	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR / 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Motion Detection - max. 4 configurable zones</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...
OSD menu	OSD menu available via recorder	...	...
Power supply	12 V DC / 410 mA	100 ... 240 V	...
Power consumption	≤ 5 W	...	...
Housing	Compact, Aluminum	Plastic	...
Color	White	White	Gray
"Index of Protection"	IP67	...	...
Operation temp	-40 °C ... 60 °C	...	...
Weight	0.39 kg	0.04 kg	0.180 kg
Dimensions	165 x 70 x 72 mm	88 x 40 x 25 mm	...
Supported languages	English, Chinese, French, Spanish, Japanese, Korean, German, Polish, Portuguese, Russian, Italian	...	...
Manufacturer / Brand	DAHUA	...	...
Guarantee	3 years	2 years	2 years