



	SWITCH POE GTX-CLM1-6-4G2G 4-PORT	IP SPEED DOME CAMERA OUTDOOR TC-H354S SPEC:23X/I/E/V3.1 - 5 Mpx 5 ... 115 mm TIANDY
		
	57.18 GBP 57.18 GBP	726.60 GBP 726.60 GBP
Standard	...	IP
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (4 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Management	✓	...
Transmission speed	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE	...
Operation modes	<ul style="list-style-type: none"> • EXTEND mode • Port Isolation 	...
Maximal output power	30 W / port PoE	...
Resolution	...	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Maximal total power	65 W	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Lens	...	5 ... 115 mm
Main features	<ul style="list-style-type: none"> • QoS - mechanisms, which provide the high quality of transmission • Spanning Tree STP/RSTP • VLAN support - Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • Port mirroring function • MTBF (Mean Time Between Faults) : 50000 h 	...
View angle	...	<ul style="list-style-type: none"> • 58 ° ... 3 ° (manufacturer data) • 55 ° ... 3.5 ° (our tests result)
Optical zoom	...	x 23
LED diodes	PWR, PoE, Link/Act	...
Digital zoom	...	x 16
Range of IR illumination	...	150 m

Video output	...	—
Certificates	CE, FCC, RoHS	...
Preset rotation speed	...	<ul style="list-style-type: none"> • 80 °/s (horizontal) • 80 °/s (vertical)
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 80 °/s (horizontal) • 0.1 °/s ... 80 °/s (vertical)
Operation temp	-10 °C ... 45 °C	...
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-16 ° ... 90 °
RS-485 interface	...	✓
Number of presets	...	500
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	S+265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> • Audio input • Audio output
Main stream frame rate	...	25 fps @ 3.7
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Memory card slot	...	Micro SD card support up to 512GB
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	192.168.2.1	DHCP or 192.168.1.2
Default admin user / password	admin / admin	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001

PC client access ports	...	3000, 3001
Port ONVIF	...	80
Intelligent image analysis	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • video tampering • detection of persons on duty • protective helmet detection • detection of people gathering • people counting • parking detection • running • detection of loitering in a given area • heat map • abandoned/missing object • double crossing the line • crossing the line (tripwire) • classification of people and vehicles • Face recognition
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Motion Detection • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions
Protections	Overvoltage \pm 4 kV	• Overvoltage protection : 6 kV

Power supply	100 ... 264 V AC, Power adapter included	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC
Power consumption	...	≤ 19.4 W
Housing	Metal	Speed Dome, Aluminum + Plastic (PC + ABS)
Color	...	White + Black
Operation temp	...	-30 °C ... 65 °C
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Weight	0.65 kg	2.2 kg
Dimensions	200 x 118 x 44 mm	Ø 161 x 276 mm (without bracket)
Supported languages	...	Polish, English, Albanian, Arabic, Korean, French, Hebrew, Spanish, Dutch, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	...	TIANDY
Guarantee	2 years	3 years