

	CABLE HDMI-2.0/SLIM 2.0 m	SOFT START MODULE SF-1	ACCESS CONTROLLER MC16-PAC-EX-1-KIT ROGER	CABLE MANAGEMENT LMA-1100X50/B
				
	1816.19 HUF 1816.19 HUF	2923.81 HUF 2923.81 HUF	173809.52 HUF 173809.52 HUF	5653.33 HUF 5653.33 HUF
Number of served transitions	...	...	1 (two-way)	...
Number of control inputs	...	1	...	...
Length	...	...	...	1100 mm
Support	...	...	RACS 5 v2 (Roger)	...
Number of power inputs	...	1	...	...
Width	...	...	...	50 mm
Number of supported readers	...	...	4 pcs	...
Number of power outputs	...	1	...	...
Depth	...	...	...	26.5 mm
Connector type	Straight plug HDMI / Straight plug HDMI	...	...	...
Battery backup support	...	...	max. 7 Ah	...
Voltage	...	230 V AC	...	...
Material	...	...	...	Aluminum
Length of the cable	2.0 m	...	...	...
Input lines	...	...	8 pcs	...
Maximal output power	...	1150 W	...	...
Color	...	...	...	Black
Output lines	...	...	8 pcs	...
Protection type	...	5 A 5/20mm delayed fuse	...	...
Connectors type	...	3 x screw terminals max. 1.5 mm ²	...	...
Montage hole diameter	...	3 mm	...	...
Class of the cable	32 AWG	...	...	...
Communication	...	...	• RS-485, • RACS 5 v2 (Roger), • Wiegand	...
HDMI standard	1.4	...	...	...
Power supply	...	...	230 V AC	...
Mounting holes distance	...	52 x 47 mm	...	...

Main features	• Very flexible • 4K resolution support • 3D image transmission • AUDIO return channel • Ethernet channel	...	• Metal housing • Power output : 1 x 0.2 A, 1 x 1.0 A • Power adapter : 24 V DC / 2.2 A, • Battery charging current : 0.3 A • Protection against deep discharge of the battery • Tamper detection - opening the enclosure • Place for battery - 12 V / 7 Ah • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)	Two-piece strip - mounting to the wall with screw plugs and covering with masking finishes
Operation temp	...	...	5 °C ... 40 °C	...
Permissible relative humidity	...	...	10 % ... 95 % (non-condensing)	...
Weight	...	0.04 kg	3.88 kg	0.67 kg
Dimensions	...	60 x 55 x 28 mm	405 x 365 x 120 mm	...
Manufacturer / Brand	...	...	ROGER	...
Guarantee	2 years	2 years	3 years	2 years

