

	POWER DISTRIBUTION UNIT AK-SP-05B AKYGA	PATCHCORD RJ45@0.2-ORANGE 0.2 m	STYROFOAM PLUG FISCHER FID-50	MULTI-MODE PIGTAIL WITH SC 50/125 CONNECTOR PIG-SC-MM	INSULATED RING TERMINAL KSIO-1.52.5/M6	TELEPHONE CABLE YKSY-3X-0.5	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-112302 L+2 TYPE 50 kA LEGRAND	13.56 MHz S50 PROXIMITY CARD IC-S50 DAHUA	SWITCH FOR IPB-5-10A-S4 5-PORT ATTE	TV OR MONITOR MOUNT AX-SATURN RED EAGLE	
											
Connector type	3543.81 HUF	241.90 HUF	321.90 HUF	348.57 HUF	88.57 HUF	196.19 HUF	19045.71 HUF	761.90 HUF	30875.24 HUF	8720.95 HUF	
Standard				SC				13.56 MHz S50			
Diameter			Ø 25 mm								
Compatibility								ISO/IEC 14443A			
Rated voltage	230 V AC / 50 Hz						230 / 400 V AC, 50 / 60 Hz				
Thickness of the Styrofoam		≥ 50 mm									
Possibility of programming the serial number (ID)								--			
Cable		UTP cat. 6 : RJ-45 plug / RJ-45 plug									
Total maximal current	10 A										
In section						100 m - Price for 1m when buying a whole roll					
Fiber optic type				50 / 125 µm - OM2							
Maximal voltage							320 V AC, 50 / 60 Hz				
Ability to write to internal memory							✓				
Maximal total load	2500 W										
Response time	< 25 ns										
Length		50 mm		1 m							
Applications					Stranded wires						
Diameter of the screw			Ø 4.5 mm / Ø 5 mm								
Serial Number overprint								--			
Number of outlets	5 grounded outlets 10A/250V										
Hole diameter					6.5 mm						
Class							1+2 type ( Class B+C )				
LAN ports								• 1 x RJ45 10/100 Base-T-Uplink • 5 x RJ45 10/100 Base-T-PoE (802.3af) / Passive PoE			
Automatic delayed fuse	10 A / 250 V										
Inner conductor						10 x Ø 0.5 mm - Cu wire					
Mounting standard										VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400 x 200, 400	
Cross section					1.5 ... 2.5 mm <sup>2</sup>						
Outer coating						PVC					
Nominal voltage of surge suppressor	250 V / 50 Hz										
Casting color						White					
Screen size range										23" ... 56"	
Bearing capacity										45 kg	
Protection level Up							1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)				
Management											
DC filter to eliminate interferences	RFI ≤ 10 dB										
Distance from mounting surface										81 ... 360 mm	
LED rhodes									Power, LAN		
Maximum energy absorption	150 J										
Switch	with light indication										
Nominal discharge current							8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)				
Length of the cable	3.0 m	0.2 m									
Tilt adjustment										12" ... 12"	
Transmission speed									10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports		
Maximum stroke current	4.5 kA						50 kA @ 8/20 µs (T2)				
Color	Black	Orange								Black	
Horizontal rotation										90° ... 90°	
Operation state indication							✓				
Rotation in the plane of the screen										--	
Housing	Plastic (ABS)						Plastic				
Operation temp	5 °C ... 50 °C										
Maximal output power								• 40 W @ Passive PoE - 1 ... 5 ports • 50 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports			
Maximal total power								90 W			
Main features		Very easy and quick assembly					Varistor	Range : ~ 10 cm	• Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55		
Power supply								180 ... 240 V AC - Built-in switching power supply			
Weight	0.372 kg	0.014 kg	0.004 kg				0.098 kg	0.006 kg	0.43 kg	4.02 kg	
Dimensions	305 x 50 x 40 mm				27.0 x 11.0 x 6.0 mm		62 x 54 x 17 mm	86 x 54 x 0.8 mm	158 x 118 x 77 mm	433 x 150 x (81 ... 360) mm	
Manufacturer / Brand	AKYGA						LEGRAND	DAHUA	ATTE	RED EAGLE	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00