

	<a href="#">POE SWITCH / EXTENDER PFT1320 3-PORT</a>	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI- AI80FQRTD 4.5 mm - 1080p</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LPA68-223</a>
			
	75.20 PLN 75.20 PLN	180.00 PLN 180.00 PLN	27.21 PLN 27.21 PLN
Mounting standard	...	...	VESA 100, 200
Scanning system	...	Progressive	...
Screen size range	...	...	23 " ... 43 "
Bearing capacity	...	...	30 kg
Optical zoom	...	—	...
LAN ports	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>	...	...
Distance from mounting surface	...	...	56 ... 378 mm
Sensor	...	1/2.9 " GC2093 1/2.9 " GC2053	...
Tilt adjustment	...	...	-10 ° ... 3 °
Matrix size	...	2.1 Mpx 2 Mpx	...
Management	—	...	...
Lens	...	4.5 mm 4.5 mm	...
Horizontal rotation	...	...	-90 ° ... 90 °
LED diodes	Link, Act	...	...
Rotation in the plane of the screen	...	...	—
Transmission speed	10 / 100 Mbps	...	...
Maximal output power	15.4 W @ port PoE - First device	...	...
Cards support	...	13.56 MHz S50	...
Keyboard built-in	...	—	...
Main features	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>	...	...
Doorbell button	...	—	...

Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p 640 x 480 px	...
View angle	...	66 ° 66 ° 90 °	...
Interface	...	USB, RS-232 TTL	...
Range	100 m - Input 100 m - Output	...	...
Maximum background illumination	...	100 000 Lux	...
Protections	—	...	...
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %	...	...
QR codes reading	...	<ul style="list-style-type: none"> <li>• 1D : EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5</li> <li>• 2D : QR Code, Data Matrix, PDF417, Aztec</li> </ul>	...
Reading distance	...	<ul style="list-style-type: none"> <li>• EAN13 (13 mm) : 30 ... 140 mm</li> <li>• Code 39 (5 mm) : 30 ... 50 mm</li> <li>• QR Code (20 mm) : 35 ... 120 mm</li> <li>• Data Matrix (10 mm) : 30 ... 70 mm</li> <li>• PDF417 (6.67 mm) : 30 ... 80 mm</li> </ul>	...
Minimal contrast	...	25 %	...
Standard	...	TCP/IP	...
Range of IR illumination	...	5 m	...
White light LED illuminator range	...	5 m	...
Temperature measurement	...	✓	...
Temperature measurement range	...	35.7 °C ... 42 °C	...
Accuracy of temperature measurement	...	± 0.3 °C	...
Temperature measurement distance	...	0.7 m ... 1.2 m	...

Face recognition distance	...	0.5 m ... 2.0 m (max 30 000 faces in the database)	...
Internal memory	...	Support storage of 50 000 records	...
Video output	...	—	...
RS-485 interface	...	✓	...
Wiegand interface	...	✓	...
Memory card slot	...	—	...
Alarm inputs / outputs	...	0 / 1	...
Audio	...	Speaker built-in	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	IPv4, TCP/IP, HTTP, MQTT, RTSP, SMTP, NTP	...
WEB Server	...	Built-in	...
ONVIF	...	—	...
Default IP address	...	DHCP / 192.168.1.88	...
Default admin user / password	...	admin / 12345	...
Web browser access ports	...	80	...
PC client access ports	...	80	...
Main features	...	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 800 x 1280 px, 8 "</li> <li>• Wiegand 34/26</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• RESET button</li> <li>• Alarm output of NO/NC relay type</li> <li>• Relay output operating modes: access control or notification of an exception</li> <li>• Built-in QR code reader</li> </ul>	...
Power supply	PoE (802.3af/at)	12 V / 2 A DC	...
Power consumption	0.3 W	≤ 18 W	...
Housing	Plastic	Compact - Metal	...
Color	...	Silver	Black
"Index of Protection"	...	—	...
Operation temp	...	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	0.05 kg	1.8 kg	1.7 kg
Dimensions	88 x 44 x 22 mm	366 x 132 x 144 mm	230 x 230 x (56 ... 378) mm

Montage hole diameter	...	35 mm	...
Length of the cable	...	65 cm	...
Supported languages	...	English, French, Spanish, Ukrainian, Italian	...
Manufacturer / Brand	...	APTI	BRATECK
Guarantee	2 years	3 years	2 years