



	<a href="#">EXTENDER EXT-POE2 PULSAR</a>	<a href="#">ACOUSTIC GLASS BREAK DETECTOR DG-457 PARADOX</a>
		
	30.43 USD 30.43 USD	25.11 USD 25.11 USD
Detection	...	Glass break detector
Standards	PoE : IEEE 802.3at, IEEE 802.3af	...
Input voltage	42 ... 57 V DC	...
Range	...	9 m - high level, 4.5 m - low level
Output voltage	42 ... 57 V DC	...
Number of inputs	1	...
Sensitivity adjustment	...	✓
Number of outputs	2	...
Connector	3 x RJ-45 socket	...
Alarm signaling	...	LED indicator, Signal to control panel
LED indicators	Link/Act	...
Relay contacts rating (resistive load)	...	150 mA / 28 V DC
Power supply	...	9 ... 16 V DC / 35 mA
Main features	...	<ul style="list-style-type: none"> <li>• detection of breaking plate, laminated or tempered glass</li> <li>• advanced dual-path microprocessor signal analysis</li> <li>• self test feature</li> <li>• Control panel BUS</li> </ul>
Supported data rates	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates : 10 / 100 Mbps - Fast Ethernet</li> </ul>	...
Color	...	White
Operation temp	...	-20 °C ... 50 °C
Output power	max. 15.4 W / port PoE max. 20 W (total)	...
Protections	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>	...
Housing	Metal	...
Operation temp. / Relative humidity	-10 ... 40 °C / 10 ... 90 %	...

Weight	0.11 kg	0.056 kg
Dimensions	81 x 77 x 26 mm	66 x 90 x 25 mm
Manufacturer / Brand	PULSAR	PARADOX
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00