



	ACCESS CONTROLLER ASC2204C-D DAHUA	EXTENDER VGA-EX-60
		
	747.22 EUR 747.22 EUR	13.32 EUR 13.32 EUR
Device type	...	Passive
Number of served transitions	4 (two-way)	...
Support	DAHUA	...
Video transmission range	...	max. 60 m
Number of supported readers	8 pcs	...
Symmetrical socket impedance	...	100 Ω
Battery backup support	max. 7 Ah	...
Input lines	20 pcs	...
Output lines	8 pcs - Relay	...
Connectors type	...	<ul style="list-style-type: none"> • 1 pcs VGA socket • 1 pcs RJ-45 shielded socket
Communication	<ul style="list-style-type: none"> • 9x RS-485, • Ethernet, • 8x Wiegand 34/26 	...
Power supply	100 ... 240 V AC	—
Resolution	...	<ul style="list-style-type: none"> • 1600 x 1200 px UXGA, • 1280 x 1024 px SXGA, • 1280 x 768 px WXGA, • 1024 x 768 px XGA, • 800 x 600 px SVGA, • 640 x 480 px VGA
Grounding	...	—

Main features	<ul style="list-style-type: none"> • Support for 4 doors (20 inputs: 4x lock state, 4x door sensor, 4x exit button, 8x alarm line) • 100000 indexed users • History of 500000 events • 128 General Purpose Schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Door Left Open and Door Forced Open alarms • Tamper detection - opening the enclosure • Watchdog built-in • Remote programming from PC • Real time clock with battery backup • Metal housing - "Index of Protection" IP20, IK rating IK04 	...
Operation temp	-30 °C ... 60 °C	0 °C ... 40 °C
Permissible relative humidity	max. 95 % (non-condensing)	≤ 85 %
Weight	2.54 kg	0.07 kg
Dimensions	272 x 337 x 90 mm	57 x 42 x 27 mm
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years