




	SWITCH POE SG-64H 4-PORT PULSAR	POWER DISTRIBUTION UNIT LE-049419 (6 OUTLETS) 1.5 m LEGRAND	POWER DISTRIBUTION UNIT PD-7/RACK
			
	127.99 EUR 127.99 EUR	39.00 EUR 39.00 EUR	17.70 EUR 17.70 EUR
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-TX - PoE (802.3af/at), • 2 x RJ45 10/100/1000 Base-TX - Uplink ports
Rated voltage	...	230 V AC / 50 Hz	230 V AC / 50 Hz
Total maximal current	...	16 A	16 A
Maximal total load	...	3680 W	3680 W
Management	—
Number of outlets	...	6 grounded outlets 16A/250V - CEE 7/5	7 x CEE 7/5
Assembly	In RACK 19" cabinets
Length of the power cable	2 m
Automatic delayed fuse	...	—	...
Nominal voltage of surge suppressor	...	275 V / 50 Hz	250 V / 50 Hz
Housing type	1 U RACK 19"
Protection level of surge suppressor	...	< 1.5 kV (L/N)	...
Nominal stroke current	...	1.5 kA (L/N) - (8/20µs)	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power	30 W / port PoE
Maximal total power	30 W
Switch	...	with light indication	two-way, with light indication
MAC addresses table	1k
Length of the cable	...	1.5 m	...

Main features	<p>There are cable glands in the housing :</p> <ul style="list-style-type: none"> • 6 pcs Ø 4 ... 8 mm • 1 pcs Ø 10 ... 14 mm 	<ul style="list-style-type: none"> • Mounting brackets for screwing the device to a flat surface or mounting with fastening ties • The body of the device rotates in the range of 180° relative to the mounting brackets • Outlets protected with a protection shutter • LED indication : Power supply, Overvoltage protection 	...
Certificates	CE
Power supply	230 V AC
Housing	Plastic, IP56	Plastic	...
Weight	1.33 kg	0.59 kg	0.72 kg
Dimensions	146 x 196 x 78 mm	423 x 66 x 100 mm	483 x 45 x 44 mm
Manufacturer / Brand	PULSAR	LEGRAND	...
Guarantee	2 years	2 years	2 years