

	ANGULAR ADAPTER IEC-G/F-G-KAT	RJ45 CONNECTOR TOOL KIT NS-468/KIT	LIVE WIRE, METAL AND WOOD DETECTOR DM-3 Virone	METER OF CAPACITANCE, INDUCTANCE AND RESISTANCE UT-603
				
	1.02 PLN 1.02 PLN	38.48 PLN 38.48 PLN	54.40 PLN 54.40 PLN	224.26 PLN 224.26 PLN
DC voltage measurement	—
AC voltage measurement	—
DC current measurement	—
AC current measurement	—
Connector type	Angular adapter - Socket IEC / Socket "F"
Impedance	75 Ω
Tested cables	...	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C), RJ12 (6P6C)
Material	Metal
Detector range	<ul style="list-style-type: none"> • Wood : 38 mm, • Metal : 50 mm, • AC live wires : 30 mm 	...
Application	...	Plug RJ45 (8P8C) , Plug RJ12 (6P6C) , Plug RJ11 (6P4C) / DEC
Resistance measurement	200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 0.001 kΩ , 20 kΩ ± (0.8% + 1) @ 0.01 kΩ , 200 kΩ ± (0.8% + 1) @ 0.1 kΩ , 2 MΩ ± (0.8% + 1) @ 0.001 MΩ , 20 MΩ ± (2.0%(RD-12) + 5) @ 0.01 MΩ 2000 MΩ @ 1 MΩ - visual measurement
Capacitance measurement	2 nF ± (1% + 5) @ 0.001 nF , 20 nF ± (1% + 5) @ 0.01 nF , 200 nF ± (1% + 5) @ 0.1 nF , 2 μF ± (4% + 5) @ 0.001 μF , 20 μF ± (4% + 5) @ 0.01 μF , 200 μF ± (4% + 5) @ 0.1 μF , 600 μF @ 1 μF - visual measurement

Inductance measurement	2 mH ± (2% + 8) @ 0.001 mH , 20 mH ± (2% + 8) @ 0.01 mH , 200 mH ± (2% + 8) @ 0.1 mH , 2 H ± (5% + 5) @ 0.001 H , 20 H ± (5% + 5) @ 0.01 H , 200 H @ 0.1 H - visual measurement
Frequency measurement	—
Square-wave signal duty ratio measurement	—
Temperature measurement	—
hFE	✓
Diode test	✓
Sound signal of the continuity test	✓
Checking TTL logic states	—
RS-232	—
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance 	...	<ul style="list-style-type: none"> • Automatic calibration after turned on, • Optical - sound signaling , 	<ul style="list-style-type: none"> • Large, readable LCD display with backlight • Hold - stopping the meter reading • Aesthetic and solid construction
Power supply	...	Battery 9 V 6LR61 (not included)	9V, type 6F22 battery - included	9V, type 6LR61 battery - included
Weight	0.010 kg	0.12 kg 0.77 kg (total)	0.139 kg - Without batteries	0.29 kg
Dimensions	...	101 x 107 x 28 mm 260 x 170 55 mm (case)	150 x 70 x 35 mm	172 x 84 x 41 mm
Manufacturer / Brand	Virone	UNI-T
Guarantee	2 years	2 years	2 years	2 years