



	BATTERY PACK DS-PM1-D TO AX PRO CONTROL PANELS Hikvision	VIDEO BALUN TR-8M
		
	31.59 CHF 31.59 CHF	26.03 CHF 26.03 CHF
Support	HIKVISION AX PRO	...
Main features	<ul style="list-style-type: none"> • Output voltage : 5.5 V DC - stabilized • Very easy and quick assembly 	...
Power supply	8 V ... 24 V DC	...
Standard	...	<ul style="list-style-type: none"> • AHD - 5 Mpx, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Device type	...	Passive
Number of channels	...	8 pcs Video
Manufacturer / Brand	Hikvision	...
SAP Code	302401878	...
Video transmission range	...	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - UTP cat. 5e
Attenuation	...	<ul style="list-style-type: none"> • 4.43 MHz @ 0.42 dB • 11 MHz @ 0.64 dB • 21 MHz @ 0.91 dB • 38 MHz @ 1.41 dB • 42 MHz @ 1.53 dB • 67.5 MHz @ 2.22 dB <p>The attenuation applies to two devices connected to each other</p>
Coaxial socket voltage range 75Ω (CVBS)	...	1 Vpp
Isolation between inputs	...	> -50 dB
CMRR (dB @ 5MHz)	...	60 dB
Coaxial socket impedance	...	75 Ω
Symmetrical socket impedance	...	100 Ω
Coaxial socket type	...	8 x BNC Plug with cable

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Symmetrical socket type	...	Cable terminals / 2 x RJ-45 (8-pin, 4 pairs) Socket
Operation temp	-10 °C ... 55 °C	-10 °C ... 70 °C
Permissible relative humidity	10 % ... 90 %	< 95 %
Weight	0.03 kg	0.32 kg
Dimensions	79 x 91 x 19 mm	185 x 58 x 25 mm
Guarantee	2 years	2 years