




	<a href="#">CABLE USB-A/USB-C/1.2M-GC 1.2 m Green Cell</a>	<a href="#">SMART THERMOSTATIC HEAD ATLO-TH2-TUYA Zigbee, Tuya Smart</a>	<a href="#">TRIPLE SMART LIGHT TOUCH SWITCH ATLO-TB3-TUYA Wi-Fi, Tuya Smart</a>
			
	4.92 EUR 4.92 EUR	31.44 EUR 31.44 EUR	10.58 EUR 10.58 EUR
Application	...	radiator valve control head	Works with lighting - switching on/off
Cable	USB-C plug / USB-A plug	...	...
Power supply	...	2 x battery 1.5 V LR6 (AA)	...
Measurement range	...	0 °C ... 60 °C	...
Length of the cable	1.2 m	...	...
Measuring accuracy	...	± 1 °C	...
Rated voltage	...	...	100 ... 240 V AC, 50 / 60 Hz
USB standard	2.0	...	...
Manual temperature control	...	5 °C ... 35 °C	...
Maximum power	...	...	300 W (for each output)
Rated current	...	...	max. 10 A
Number of buttons	...	...	3 (touch)
Number of outputs	...	...	3
Connector type	...	...	screw terminals
Wireless	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	...	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>
Cable diameter	~ 3.5 mm	...	...
Manufacturer / Brand	Green Cell	...	...

Main features	<ul style="list-style-type: none"> <li>• High noise immunity</li> <li>• 100% copper conductor</li> <li>• 2 x Cu - AWG 30 : Data + 2 x Cu - AWG 23 : Power supply</li> <li>• Solid workmanship</li> <li>• Illuminated USB-C plug, Backlight color : Green</li> <li>• Double shielding of the cable</li> <li>• Kevlar fiber reinforcement</li> </ul>	<ul style="list-style-type: none"> <li>• Possibility of manual change of the valve position,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Temperature Sensor : NTC thermistor</li> <li>• LED display</li> <li>• LED indication</li> <li>• Heating suppression if a window is open</li> <li>• Anti-scale function</li> <li>• Child Lock - securing the device against children</li> <li>• Time mode</li> <li>• Anti-freezing function</li> <li>• Failure signaling</li> <li>• Low battery level alarm</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• LED indication</li> <li>• Backlit, touch control panel</li> <li>• The product does not fit standard mounting boxes with a diameter of 60 mm</li> </ul>
Housing	...	Plastic	Plastic + Acrylic glass (plexiglass)
Color	Black	White	White
Permissible relative humidity	...	...	≤ 80 %
Operation temp	...	0 °C ... 50 °C	-20 °C ... 50 °C
Weight	0.03 kg	0.146 kg	0.142 kg
Dimensions	...	Ø 55 x 95 mm	86 x 86 x 34 mm
Guarantee	2 years	2 years	2 years