








	TV OR MONITOR MOUNT BRATECK-LPA68-221	SURFACE HOUSING DS- KAB02 Hikvision	UNIVERSAL HERMETIC ENCLOSURE OPX-1-GY SATEL	POWER GENERATOR FH-4001R_3800 W Honda GX 270 FOGO	SWITCH POE GTX-A1-10-8Z 8-PORT	SWITCH POE IP-9-11-L2 8- PORT ATTE	EXTENSION CORD WITH GROUNDING PS-3X1.5-20M/ORANGE 20 m
							
	10.55 CAD 10.55 CAD	60.29 CAD 60.29 CAD	7.05 CAD 7.05 CAD	1728.60 CAD 1728.60 CAD	95.34 CAD 95.34 CAD	265.53 CAD 265.53 CAD	22.19 CAD 22.19 CAD
Nominal power	...	...	...	3800 W	...	...	...
Length of the cable	...	...	...	...	...	...	20 m
Support	...	...	AXD-200, XD-2	...	...	...	...
Maximum power	...	...	...	4200 W	...	...	...
Wire gauge	...	...	...	...	...	...	3 x 1.5 mm <sup>2</sup>
Tamper protection	...	...	Tamper contact working with the AXD-200, XD-2 detectors	...	...	...	...
Output voltage	...	...	...	230 V AC	...	...	...
Application	...	...	...	...	...	...	...
Mounting standard	VESA : 100, 200, 200x100	DS-KV8X02-1M	...	...	...	...	...
Rated voltage	...	...	...	...	...	...	230 V AC / 50 Hz
Total maximal current	...	...	...	...	...	...	16 A
"Index of Protection"	...	...	IP65	...	...	...	...
Built-in voltmeter	...	...	...	---	...	...	...
Screen size range	23 " ... 43 "	...	...	...	...	...	...
Maximal total load	...	...	...	...	...	...	3680 W
Number of outlets	...	...	...	2 pcs - single-phase	...	...	1 x CEE 7/5
Output frequency	...	...	...	50 Hz	...	...	...
LAN ports	...	...	...	...	<ul style="list-style-type: none"> <li>• 8 x RJ45 ( 1 x Hi-PoE + 7 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>	...
Bearing capacity	30 kg	...	...	...	...	...	...
Fuse	...	...	...	...	...	---	---
Material	...	Stainless steel SUS201, SGCC	Plastic (polycarbonate)	...	...	...	...
Voltage stabilization	...	...	...	AVR	...	...	...
Distance from mounting surface	56 ... 204 mm	...	...	...	...	...	...
Switch	...	...	...	...	...	---	---
External dimensions	...	193 x 106 x 75 mm	...	...	...	...	...
12V DC output	...	...	...	---	...	...	...
Engine power	...	...	...	8 HP	...	...	...
Tilt adjustment	-8 ° ... 5 °	...	...	...	...	...	...
SAP Code	...	305700160	...	...	...	...	...
Engine capacity	...	...	...	270 cm <sup>3</sup>	...	...	...
Horizontal rotation	-90 ° ... 90 °	...	...	...	...	...	...
Rotation in the plane of the screen	---	...	...	...	...	...	...
Color	Black	Light gray	Gray	...	---	---	Orange
Management	...	...	...	...	---	---	---
Engine type	...	...	...	Honda GX 270 1 cylinder, 4 stroke, gasoline, air cooled	...	...	...
Starting the engine	...	...	...	Manual	...	...	...
Noise level during operation	...	...	...	96 dB	...	...	...
Average fuel consumption	...	...	...	2.2 l/h - 75 % power	...	...	...
LED diodes	...	...	...	...	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	Power, LAN	...
Fuel tank capacity	...	...	...	5.3 l	...	...	...
Fuel gauge	...	...	...	---	...	...	...
Transmission speed	...	...	...	...	10 / 100 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	...
Maximal output power	...	...	...	...	<ul style="list-style-type: none"> <li>• 60 W / port Hi-PoE - Port 1</li> <li>• 30 W / port PoE - 2 ... 8 ports</li> </ul>	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>	...
Operation modes	...	...	...	...	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> </ul>	...
Maximal total power	...	...	...	...	120 W	96 W	...
MAC addresses table	...	...	...	...	1k	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	...	<ul style="list-style-type: none"> <li>• Key for opening the enclosure included</li> <li>• Output for FPX-1 flood probe</li> </ul>	<ul style="list-style-type: none"> <li>• Low oil level indicator light</li> <li>• Overload protection</li> </ul>	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Full Duplex: IEEE802.3x, Half Duplex: Back Pressure</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement</li> </ul>	...
Certificates	...	...	...	...	CE, FCC Class B	...	...
Protections	...	...	...	...	Overvoltage $\pm$ 4 kV	...	...
Power supply	...	...	...	...	100 ... 265 V AC	230 V AC - cable terminals	...
Manufacturer / Brand	BRATECK	Hikvision	SATEL	FOGO	...	ATTE	...
Operation temp	...	...	...	...	-10 °C ... 45 °C	...	...
Weight	1.03 kg	1.072 kg	0.05 kg	56 kg	0.76 kg	1.05 kg	1.57 kg
Dimensions	230 x 230 x (56 ... 205) mm	...	157 x 29 x 28 mm	650 x 520 x 490 mm	210 x 150 x 35 mm	248 x 222 x 96 mm	...
Guarantee	2 years	3 years	2 years	3 years - The condition is to conduct paid service every year - a warranty inspection at authorized Honda or FOGO service stations, otherwise 12 months	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00