



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TLM-IL- A-0280B-S2 - 5 Mpx 2.8 mm DAHUA</a>	<a href="#">MOUNT RACK FRAME U19-2U/165</a>
		
	98.40 USD 98.40 USD	33.05 USD 33.05 USD
Internal depth	...	157 mm
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 4 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	...
Sensor	Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	106 °	...
Range of IR illumination	40 m	...
White light LED illuminator range	40 m	...
IR illuminator power adjustment	Automatic	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	...
OSD menu	✓	...

Main features	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Power supply	12 V DC / 380 mA	...
Power consumption	≤ 4.5 W	...
Housing	Compact Plastic + Metal	...
Color	White + Black	Black
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.3 kg	0.96 kg
Dimensions	198 x 80 x 76 mm	520 x 94 x 170 mm - RACK 19 " x 2 U
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years