







	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps	EXPANSION PLUG JPK-12X220/M5 EBOLT	EXPANSION PLUG KS-12/8X120 KLIMAS	CONNECTOR FOR LED STRIPS UOS-COB-8W-CS 8 mm	SMART LED LIGHTING CONTROLLER WLIGHTBOX-S-V2/BLEBOX Wi-Fi, 12 ... 24 V DC
						
	103.32 USD 103.32 USD	117.21 USD 117.21 USD	2.14 USD 2.14 USD	0.53 USD 0.53 USD	0.86 USD 0.86 USD	23.08 USD 23.08 USD
Sensor	SmartSens CMOS - 2 Mpx
Strip width	8 mm	...
Resolution	1920 x 1080 px - 1080p
Length of the cable	140 mm	...
Rated voltage	12 ... 24 V DC
Lens	2.0 mm F1.2
Maximal total load	120 W
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized mounting screw, Steel galvanized 	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized
Drilling diameter	12 mm	12 mm
View angle	140 °
Total maximal current	5 A
Expansion plug length	215 mm	80 mm
Number of inputs	1
Number of outputs	1
Connector type	screw terminals
Screw dimensions	Ø 8 x 220 mm, Internal thread M5	Ø 8 x 120 mm, SW-13
IR illuminator	5 ... 10 m
LED illuminator	—
Screw	Ø 5 x 16 mm
proximity reader built-in	Unique EM 125kHz
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Application	for Styrofoam 150 mm	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	Works with LED lighting - COB LED strips	Works with LED lighting - single-color (MONO) 12-24V LED strips
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Frequency range	...	<ul style="list-style-type: none"> Wi-Fi : 2.4 GHz, 5 GHz, LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Network interface	<ul style="list-style-type: none"> 10/100 Mbps Fast Ethernet, RJ-45 socket 2.4 GHz Wi-Fi
Antenna type	...	<ul style="list-style-type: none"> 4 x Omnidirectional antenna Wi-Fi, Integrated, 2 x Omnidirectional antenna 4G LTE, Integrated
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS
Standards	...	IEEE 802.11 b/g/n/ac
Image compression method	H.265 / H.264
Supported audio formats	G.711
Baud rates	...	<ul style="list-style-type: none"> Wi-Fi : 866 Mbps + 300 Mbps, LTE Cat. 6 : 300 Mbps / 50 Mbps
LAN ports	...	<ul style="list-style-type: none"> 1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN
Manufacturer / Brand	EBOLT	KLIMAS	MW Lighting	BleBox

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN
SIM socket	...	1 x mini SIM
DDNS	...	✓
DHCP server	...	✓
Firmware update	...	✓
Protections	...	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Management interface	...	Web browser
Transmitter power	...	< 20 dBm
Main features	...	<ul style="list-style-type: none"> Built-in 5-port switch RESET button Remote management 	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, Lighting on/off and brightness control, Absence mode - enables random turn on and off the lighting simulating the presence of household members, µWiFi technology support
Main features	<ul style="list-style-type: none"> ATLO-DBC5/CHIME wireless support Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay Micro SD memory cards up to 256GB support (possible local recording) Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, Motion Detection, PIR detector, Indoor proximity cards and key-fobs reader, ICR - Movable InfraRed filter Day/night mode, Microphone built-in, Speaker built-in, Bidirectional communication, Noise and echo reduction Full support via network 5 on-line users, Possibility to work in cloud - you don't need to redirect the ports, Video PUSH personal messaging - Motion Detection, Video recording - Motion Detection, Doorbell button, Automatic events notification via Email messages Lock control - Relay output Tamper protections Google Home, Amazon Echo compliance
Mount	Surface-mounted
Power supply	<ul style="list-style-type: none"> 12 V DC / 1 A (power adapter included) 48 V PoE (802.3af) 	12 V DC / 1 A (power adapter included)
Housing	Aluminum + Plastic (ABS)	Plastic	Plastic
Color	Silver	Transparent	Black
"Index of Protection"	IP44	—	IP20
Operation temp	-20 °C ... 55 °C	-20 °C ... 50 °C
Weight	<ul style="list-style-type: none"> 0.22 kg - Wireless Video Doorbell 0.046 kg - rain cover 	0.42 kg	0.002 kg	0.014 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	238 x 149 x 33 mm	12 x 10 x 5 mm	35 x 24 x 18 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00