


	CABLE OUTLET DPK1.01/49-SIMON54	POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	IP HYBRID THERMAL IMAGING CAMERA DS-2TD2628T-3/OA 3.6 mm - 720p, 4.3 mm - 4 Mpx Hikvision
				
	28.66 PLN 28.66 PLN	67.25 PLN 67.25 PLN	150.96 PLN 150.96 PLN	5031.00 PLN 5031.00 PLN
Rated voltage	...	230 V AC / 50 Hz	230 V AC	...
Rated current	10 A (total)	...
Support	Simon 54 product series, for Nature, Premium frames
Total maximal current	...	10 A
Number of modules	1
Pixel pitch	12 µm
Maximal total load	...	2300 W
Response time	...	< 25 ns	< 25 ns	...
Thermal sensitivity (NETD)	≤ 40 mK @ F1.0
Spectral range	8 µm ... 14 µm
Color palettes	✓
Automatic delayed fuse	...	10 A / 250 V
Main features	<ul style="list-style-type: none"> • Cable diameter : 6.2 ... 14.5 mm • Claw or screw mounting • Installation in flush-mounted enclosures • Aesthetic and solid construction
Leak current	...	< 0.5 mA	< 0.5 mA	...
Number of outlets	...	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V	5 grounded outlets 10A/250V	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz	250 V / 50 Hz	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	...
Nominal stroke current	...	2 kA (L/N) - (8/20µs)	2.5 kA (L/N) - 8/20 µs	...
Switch	...	two-way, with light indication	two-way, with light indication	...
Maximum stroke current	...	6.5 kA (L/N) - (8/20µs)	6.5 kA (L/N) - 8/20 µs	...
Length of the cable	...	1.45 m	2.7 m	...
Temperature measurement	<ul style="list-style-type: none"> • Spot • Line • Area max. 21 positions
Temperature measurement range	-20 °C ... 550 °C
Accuracy of temperature measurement	± 2 °C
Sensor	Uncooled VOx microbolometer 1/2.7 " Progressive Scan CMOS
Matrix size	256 x 192 px 4 Mpx
Lens	3.6 mm 4.3 mm
View angle	50 ° 84 °
Optical zoom	— —
Digital zoom	2x, 4x —

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Range of IR illumination	30 m
White light LED illuminator range	30 m
Resolution	1280 x 720 - 720p , 704 x 576 640 x 512 320 x 240 2688 x 1520 - 4 Mpx 1920 x 1080 - 1080p 1280 x 720 - 720p
Standard	IP
Video output	CVBS, SPOT output : 1.0 Vpp / 75 Ω
RS-485 interface	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	H.265 / H.264 / MJPEG
Alarm inputs / outputs	2 / 2
Audio	<ul style="list-style-type: none"> • External microphone input / Audio input, • Audio output, • Bi-directional audio streaming support, • Speaker built-in
Main stream frame rate	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mobile phones support	<ul style="list-style-type: none"> • Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream VIDEO CAMERA : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ THERMAL IMAGING CAMERA : rtsp://user:password@192.168.1.64:554/Streaming/Channels/201/ • Sub stream VIDEO CAMERA : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ THERMAL IMAGING CAMERA : rtsp://user:password@192.168.1.64:554/Streaming/Channels/202/
Intelligent image analysis	<ul style="list-style-type: none"> • IVS analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area • object detection (people, vehicle) • fire detection • Smoke detection



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • DDE (Digital Detail Enhancement) - the function automatically optimizes the contrast of the thermal image in high-dynamic scenes - small differences in the temperature distribution of the examined object are highlighted • Sun-reflection filter • Temperature measurement • Intelligent alarm linked to turning on white light and loudspeaker • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • The ANR (Automatic Network Replenishment) function - ensures integrity of recording data in the event of network failures. It bases on automatic saving the recording data to microSD card inserted inside the camera, and after failure is end, the recorded data are automatically synchronized with the recorder
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges : 4 kV • Overvoltage limiter, Overvoltage protection
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC, • 24 V AC
Power consumption	≤ 8.5 W
Housing	Non-halogen plastic, PC	Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	Compact - Metal
Color	Matt black	White
"Index of Protection"	IP20	IP67
Mechanical protection class	IK10
Operation temp	-40 °C ... 65 °C
Weight	0.05 kg	0.44 kg	0.59 kg	1.76 kg
Dimensions	<ul style="list-style-type: none"> • 75 x 75 x 55 mm • 22 mm - mounting depth 	370 x 65 x 44 mm	383 x 58 x 55 mm	358.3 x 113.5 x 115.2 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	KONTAKT Simon	Hikvision
SAP Code	305401691
Guarantee	6 years	2 years	2 years	3 years