



	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	POWER DISTRIBUTION UNIT ACAR-S8-DUAL
		
	36.25 EUR 36.25 EUR	23.91 EUR 23.91 EUR
Rated voltage	230 V AC	230 V AC / 50 Hz
Rated current	10 A (total)	...
Nominal load current	...	10 A (total)
Nominal voltage of surge suppressor	250 V / 50 Hz	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)
Automatic delayed fuse	...	✓
Nominal stroke current	2.5 kA (L/N) - 8/20 μs	2 kA (L/N) - 8/20 μs
Leak current	< 0.5 mA	...
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	6.5 kA (L/N) - 8/20 μs
Number of outlets	5 grounded outlets 10A/250V	8 grounded outlets 10A/250V
Response time	< 25 ns	< 25 ns
Switch	two-way, with light indication	two-way, with light indication
Length of the cable	2.7 m	1.4 m
Housing	RACK 19", 1U, Plastic - non-flammable	Plastic - non-flammable
Weight	0.59 kg	0.52 kg
Dimensions	383 x 58 x 55 mm	445 x 54 x 55 mm
Guarantee	2 years	2 years