




	NVR NVR302-32S 32 CHANNELS UNIVIEW	CONNECTION BOX PUH-RJ45/6
		
	818.68 AUD 818.68 AUD	9.38 AUD 9.38 AUD
Number of intakes	...	2
Standard	TCP/IP	...
Connectors	...	2 x RJ-45 socket
"Index of Protection"	...	IP67
Supported resolutions	max. 8.3 Mpx 4K UHD - 3840 x 2160 px	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Cable diameter	...	Ø 4 ... Ø 7 mm
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Application	...	Hermetic connection of two RJ45 patchcords - It is compatible with Category 6
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	Ultra 265 / H.265 / H.264	...
Bitrate	max. 160 Mbps	...
Supported hard drives	2 x 8 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9/16 channel synchronous playback	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...
Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP	...
ONVIF	✓	...

Default IP address	DHCP or 192.168.1.30	...
Default admin user / password	admin / 123456	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream	...
USB	2 x USB 2.0 1 x USB 3.0	...
Serial ports	—	...
Alarm inputs / outputs	—	...
PTZ control	PTZ Uniview cameras	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	Functions implemented in cooperation between the recorder and cameras that support these functions • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, scene changing, abandoned/missing object, objects tracking, people counting, crowd gathering estimation • Human detection • VIDEO signal loss alarm • Support ANR function • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 3.33 A (power adapter included)	...
Power consumption	max. 15 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...

Weight	1.73 kg	0.05 kg
Dimensions	380 x 322 x 53 mm	133 x 30 x 30 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00