





| | POWER DISTRIBUTION UNIT PR-1.5M-3G/W (3 OUTLETS) 1.3 m | EXTENSION CABLE PS-2X1.5-50M/ORANGE 50 m | HOOK & LOOP TAPE ON-OFF-TAPE/1MX20/WHITE TESA | IP CAMERA DS-2CD2387G2P-LSU/SL(4MM)(C)/BLACK PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm Hikvision |
|-----------------------------------|---|---|---|---|
| |  |  |  |  |
| | 88.53 CZK 88.53 CZK | 699.38 CZK 699.38 CZK | 91.49 CZK 91.49 CZK | 15684.34 CZK 15684.34 CZK |
| Standard | ... | ... | ... | TCP/IP |
| Length | ... | ... | 1 m | ... |
| Sensor | ... | ... | ... | 2 x 1/1.8 " Progressive Scan CMOS |
| Width | ... | ... | 20 mm | ... |
| Rated voltage | 220 ... 240 V AC / 50 Hz | 230 V AC / 50 Hz | ... | ... |
| Total maximal current | 10 A | 10 A | ... | ... |
| Mounting methods | ... | ... | self-adhesive tape | ... |
| Maximal total load | 2500 W | 2500 W | ... | ... |
| Matrix size | ... | ... | ... | 2 x 3.7 Mpx - 8 Mpx (total) |
| Number of outlets | 3 grounded outlets 10A/250V CEE 7/5 | 1 x CEE 7/17 | ... | ... |
| Scanning system | ... | ... | ... | Progressive |
| Fuse | — | — | ... | ... |
| Switch | — | — | ... | ... |
| Wire gauge | 3 x 1.5 mm ² | 2 x 1.5 mm ² | ... | ... |
| Resolution | ... | ... | ... | 5120 x 1440 - 7.4 Mpx |
| Length of the cable | 1.3 m | 50 m | ... | ... |
| Lens | ... | ... | ... | 2 x 4 mm |
| View angle | ... | ... | ... | 180 ° (horizontal) 44 ° (vertical) |
| White light LED illuminator range | ... | ... | ... | 30 m |
| RS-485 interface | ... | ... | ... | — |
| Image compression method | ... | ... | ... | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Alarm inputs / outputs | ... | ... | ... | 1 / 1 |
| Audio | ... | ... | ... | <ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Digital Noise Reduction |
| Main stream frame rate | ... | ... | ... | 20 fps @ 7.4 Mpx |
| Network interface | ... | ... | ... | 10/100 Base-T (RJ-45) |
| Memory card slot | ... | ... | ... | Micro SD memory cards up to 256GB support (possible local recording) |
| Mobile phones support | ... | ... | ... | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect |
| Default admin user / password | ... | ... | ... | admin / - The administrator password should be set at the first start |
| Default IP address | ... | ... | ... | 192.168.1.64 |
| Web browser access ports | ... | ... | ... | 80 |
| PC client access ports | ... | ... | ... | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports | ... | ... | ... | 8000 |
| Port ONVIF | ... | ... | ... | 80 |
| RTSP URL | ... | ... | ... | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization |
| WEB Server | ... | ... | ... | Built-in |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | |
|------------------------------|------------------|---------|----------|---|
| Max. number of on-line users | ... | ... | ... | 6 |
| ONVIF | ... | ... | ... | ✓ |
| Main features | ... | ... | ... | <ul style="list-style-type: none"> • Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Active deterrence function - Light and sound alarm • White light (LED) illuminator built-in : 4 LEDs • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable: brightness, contrast, saturation • Motion Detection - classification of people and vehicles |
| Power supply | ... | ... | ... | <ul style="list-style-type: none"> • 12 V DC / 790 mA, • PoE (802.3af) |
| Power consumption | ... | ... | ... | <ul style="list-style-type: none"> • ≤ 9.5 W @ 12 V DC • ≤ 10.5 W @ PoE |
| Housing | Plastic | ... | ... | Compact, Metal |
| Color | White | Orange | White | Black |
| Vandal-proof | ... | ... | ... | — |
| "Index of Protection" | ... | ... | ... | IP67 |
| Operation temp | ... | ... | ... | -30 °C ... 60 °C |
| Weight | 0.29 kg | 3.6 kg | 0.029 kg | 1.28 kg |
| Dimensions | 154 x 54 x 39 mm | ... | ... | Ø 156 x 155.3 mm |
| Supported languages | ... | ... | ... | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| SAP Code | ... | ... | ... | 311323800 |
| Manufacturer / Brand | ... | ... | TESA | Hikvision |
| Guarantee | 2 years | 2 years | 2 years | 3 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00