





	<a href="#">IP VANDALPROOF CAMERA DS-2CD2647G2HT-LIZS(2.8-12MM)(EF) ColorVu - 4 Mpx MOTOZOOM Hikvision</a>	<a href="#">SIDE WALL MOUNT UML-32H32</a>	<a href="#">CYLINDRICAL MAGNETIC CONTACT B-2-BR SATEL</a>	<a href="#">AHD_HD-CVI_HD-TVI_PAL CAMERA DS-2CE76H0T-ITPF(2.8MM)(C) - 5 Mpx Hikvision</a>
				
	631.49 EUR 631.49 EUR	6.77 EUR 6.77 EUR	2.64 EUR 2.64 EUR	59.86 EUR 59.86 EUR
Material	...	Metal	...	...
Detection	...	...	Opening the door or window	...
Diameter	...	Ø 32 mm	...	...
Maximum reed switched voltage	...	...	100 V	...
Height	...	144 mm	...	...
Maximal switched current	...	...	500 mA	...
Distance from mounting surface	...	292 mm	...	...
Make distance	...	...	19 mm	...
Standard	TCP/IP	...	...	AHD / HD-CVI / HD-TVI / CVBS
Break distance	...	...	40 mm	...
Sensor	1/1.8 " Progressive Scan CMOS	...	...	Progressive Scan CMOS
Mount	...	4 x Expansion plugs	...	...
Matrix size	4 Mpx	...	...	5 Mpx
Main features	...	<ul style="list-style-type: none"> <li>• Easy and universal mounting system</li> <li>• The whole galvanized</li> </ul>	...	...
White light LED illuminator range	60 m	...	...	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...	...	...
Resolution	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...	<ul style="list-style-type: none"> <li>• 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-TVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>
Range of IR illumination	60 m	...	...	20 m
IR illuminator power adjustment	...	...	...	Automatic
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...
Lens	2.8 ... 12 mm Motozoom	...	...	2.8 mm
Alarm inputs / outputs	1 / 1	...	...	...
View angle	<ul style="list-style-type: none"> <li>• 115 ° ... 42 ° (manufacturer data)</li> <li>• 105 ° ... 40 ° (our tests result)</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• 85 ° (manufacturer data)</li> <li>• 83 ° (our tests result)</li> </ul>
IR illuminator support	...	...	...	ICR - Movable InfraRed filter
Main stream frame rate	25 fps @ 4 Mpx	...	...	...
Network interface	10/100 Base-T (RJ-45)	...	...	...
WEB Server	Built-in	...	...	...
Video output	...	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Max. number of on-line users	6	...	...	...
Audio	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Noise suppression and echo cancellation</li> <li>• Compliance with the AAC standard</li> </ul>	...	...	—
ONVIF	✓	...	...	...
OSD menu	...	...	...	OSD menu available via recorder

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Motozoom lens</li> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
Mobile phones support	<ul style="list-style-type: none"> <li>Port no.: 8000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...	...	...
Default IP address	192.168.1.64	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...
Web browser access ports	80	...	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...	...
Mobile client access ports	8000	...	...	...
Port ONVIF	80	...	...	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 1.2 A</li> </ul>	...	...	12 V DC / 340 mA
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 18 W @ PoE</li> <li>• ≤ 14.5 W @ 12 V DC</li> </ul>	...	...	≤ 4.3 W
Housing	Compact, Metal	...	...	Dome, Plastic
Color	White	...	Brown	White
"Index of Protection"	IP67	...	...	IP67
Vandal-proof	IK10	...	...	—
Operation temp	-30 °C ... 60 °C	...	...	-40 °C ... 60 °C
Weight	1.53 kg	...	0.01 kg	0.15 kg
Dimensions	298 x 98 x 96 mm	...	Ø 11 x 14.5 mm	Ø 85 x 79 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...	...	...
Manufacturer / Brand	Hikvision	DELTA	SATEL	Hikvision
SAP Code	311323994	...	...	300613619
Guarantee	3 years	3 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00