



	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC6624SR-X33-VF LightHunter - 4 Mpx 4.5 ... 148.5 mm UNIVIEW</a>	<a href="#">IP CAMERA F4C-PV Wi-Fi. Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA</a>
		
	3167.41 AUD 3167.41 AUD	73.37 AUD 73.37 AUD
Standard	TCP/IP	IP
Matrix size	4 Mpx	...
Optical zoom	x 33	...
Resolution	2688 x 1520 - 4 Mpx	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Digital zoom	x 16	...
Sensor	1/2.8 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Video output	✓	...
Lens	4.5 ... 148.5 mm	2.8 mm
View angle	51 ° ... 2.5 °	98 °
Range of IR illumination	150 m	30 m
Preset rotation speed	• 300 °/s (horizontal) • 240 °/s (vertical)	...
White light LED illuminator range	...	30 m
S/N ratio	...	> 56 dB
Rotation speed (manual control)	• 0.1 °/s ... 200 °/s (horizontal) • 0.1 °/s ... 200 °/s (vertical)	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	✓	...
Number of presets	1024	...
Horizontal scan	✓	...
Route settings	16	...
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	2 / 1	—
Audio	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	• Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Audio output • Audio detection
Main stream frame rate	25 fps @ 4 Mpx	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)	• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45)
WEB Server	Built-in	Built-in
Max. number of on-line users	32	6
ONVIF	✓	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)

Mobile phones support	Access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	37777
Mobile client access ports	80	37777
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Configurable Privacy Zones - 24</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Home Position - set the camera to the specified position if no operator activity for a specified dwell time</li> <li>• Overvoltage protection : 6 kV</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, crowd gathering estimation, people counting</li> </ul>	<ul style="list-style-type: none"> <li>• Active deterrence function</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones - Human detection</li> <li>• Privacy zones - max. 4</li> </ul>



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 24 V DC / 2.5 A (power adapter included),</li> <li>• 24 V AC</li> </ul>	12 V DC / 550 mA
Power consumption	≤ 25 W	≤ 6.6 W @ 12 V DC
Housing	Speed Dome, Metal	Compact - Plastic
Color	White	White + Black
Operation temp	-40 °C ... 70 °C	-40 °C ... 60 °C
"Index of Protection"	IP66	IP67
Vandal-proof	—	—
Weight	5.31 kg	0.25 kg
Dimensions	Ø 227 x 385 mm	131 x 78 x 97 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	Polish, English
Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00