






	<a href="#">MULTI-MODE PATCHCORD PC-2SC/2SC-MM 1 m</a>	<a href="#">CHARACTER GENERATOR CONVERTER OSD PORT-22</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA APTI- H52C41-2812W - 8.3 Mpx 4K UHD 2.8 ... 12 mm</a>	<a href="#">ROUTER WIFI RG- EG105GW-X Wi-Fi 6, 574 Mbps + 2404 Mbps REYEE</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)</a>
					
	5.73 CAD 5.73 CAD	35.52 CAD 35.52 CAD	105.97 CAD 105.97 CAD	351.31 CAD 351.31 CAD	87.20 CAD 87.20 CAD
Maximal load power	...	...	...	...	2300 W
Support	...	OSD-50HD	...	...	...
Frequency range	...	...	...	2.4 GHz, 5 GHz	...
Nominal voltage	...	...	...	...	230 V AC / 50 Hz
Number of video inputs	...	1 x Cable terminals	...	...	...
Connector type	SC/UPC <-> SC/UPC, Duplex	...	...	...	...
Standard	...	...	AHD, HD-CVI, HD-TVI, PAL	...	...
Fuse	...	...	...	...	10 A / 250 V
Number of video outputs	...	1 x Cable terminals	...	...	...
Sensor	...	...	1/2.5 " Progressive Scan CMOS	...	...
Fiber optic type	50 / 125 µm Multi-mode fibers	...	...	...	...
Switch	...	...	...	...	two-way
Range RS-485	...	1200 m terminal connector	...	...	...
Matrix size	...	...	8.3 Mpx	...	...
Total insertion loss	≤ 0.30 dB	...	...	...	...
Leak current	...	...	...	...	< 0.5 mA
Built-in stabilizer	...	✓	...	...	...
Response time	...	...	...	...	< 25 ns
Antenna type	...	...	...	2x2 MIMO - built-in • 5 dBi @ 2.4 GHz • 5 dBi @ 5 GHz	...
PCB casing	...	—	...	...	...
Nominal voltage of surge suppressor	...	...	...	...	250 V
Protection level	...	...	...	...	1.3 kV (L/N)
Length	1 m	...	...	...	...
Nominal stroke current	...	...	...	...	2 kA (L/N) - (8/20µs)
Maximum stroke current	...	...	...	...	6.5 kA (L/N) - (8/20µs)
Standards	...	...	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6	...
Electric shock protection system	...	...	...	...	Ground connectors (pins) connected with ground wire of AC mains
Number of output outlets	...	...	...	...	• 1 MASTER outlet, two- contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet
Baud rates	...	...	...	574 Mbps @ 2.4 GHz + 2404 Mbps @ 5 GHz	...
Length of the cable	...	...	...	...	1.45 m

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Communication	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RS-485 TTL,</li> <li>• MODBUS,</li> <li>• Arduino,</li> <li>• STM Nucleo,</li> <li>• Service buttons - 6 pcs</li> </ul>	...	...	...
LAN ports	...	...	...	<ul style="list-style-type: none"> <li>• 1 x LAN 10/100/1000 Mbps (RJ-45)</li> <li>• 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)</li> </ul>	...
WAN interface	...	...	...	1 x WAN x 10/100/1000 Mbps (RJ-45)	...
Communication using optional devices	...	<ul style="list-style-type: none"> <li>• RS-485 switch</li> <li>• Micro SD - Card</li> </ul>	...	...	...
LED indicators	...	...	...	Status, Link/Act, Mesh	...
DDNS	...	...	...	✓	...
DHCP server	...	...	...	✓	...
Port USB	...	...	...	✓	...
Firmware update	...	...	...	✓	...
Power supply PoE	...	...	...	—	...
Resolution	...	...	<ul style="list-style-type: none"> <li>• 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps,</li> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps,</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>	...	...
Range of IR illumination	...	...	60 m	...	...
IR illuminator power adjustment	...	...	Automatic	...	...
Lens	...	...	2.8 ... 12 mm	...	...
Protections	...	...	...	<ul style="list-style-type: none"> <li>• TCP scan blocking</li> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> <li>• Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks</li> </ul>	...
Management interface	...	...	...	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Rejee application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...
View angle	...	...	<ul style="list-style-type: none"> <li>• 92 ° ... 27 ° (manufacturer data)</li> <li>• 100 ° ... 40 ° (our tests result)</li> </ul>	...	...
S/N ratio	...	...	> 50 dB	...	...
Mobile phones support	...	...	...	<ul style="list-style-type: none"> <li>Android: Free application <a href="#">Ruijie Rejee</a></li> <li>iOS (iPhone): Free application <a href="#">Ruijie Rejee</a></li> </ul>	...
Video output	...	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Day/Night mode - configurable</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...
Main features	<ul style="list-style-type: none"> <li>• LSZH (Low Smoke Zero Halogen) coating - means small amount of toxic gases emitted during combustion</li> <li>• Multimode fibers OM2</li> <li>• Cable diameter : 2.0 mm</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• Support for Reyee Mesh technology</li> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• Reboot schedule</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>	...
OSD menu	...	...	✓	...	...
Power supply	...	12 V / 200 mA (power adapter not included)	12 V DC / 420 mA	100 ... 240 V AC, 50 / 60 Hz	...
Power consumption	...	...	≤ 5 W	≤ 20 W	...
Housing	...	...	Compact - Metal	...	Plastic - non-flammable
Color	...	...	White	...	...
"Index of Protection"	...	...	IP67	...	...
Operation temp	...	...	...	0 °C ... 40 °C	...
Operation temp	...	...	-20 °C ... 60 °C	...	...
Permissible relative humidity	...	...	...	10 % ... 90 % (non-condensing)	...
Weight	...	0.03 kg	0.68 kg	1.1 kg	0.56 kg
Dimensions	...	90 x 48 x 20 mm	210 x 88 x 84 mm	315 x 188 x 188 mm	447 x 55 x 53 mm
Supported languages	...	...	Polish, English	...	...
Manufacturer / Brand	...	DELTA	APTI	RUIJIE / REYEE	...
Guarantee	2 years	3 years	2 years	2 years	2 years