





	<a href="#">TOOL BOX KHV40P</a>	<a href="#">SWITCH PFS3005-5GT-L-V2 5-PORT DAHUA</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LP77-44T</a>	<a href="#">ACCESS CONTROL PANEL CPR32-SE-BRD ROGER</a>
				
	8.06 EUR 8.06 EUR	13.15 EUR 13.15 EUR	11.82 EUR 11.82 EUR	155.45 EUR 155.45 EUR
LAN ports	...	5 x RJ45	...	...
Material	Plastic - mixture of increased strength polymers	...	...	...
Inputs	...	...	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 32</li> </ul>
Management	...	—	...	...
LED diodes	...	Power, Link/Act	...	...
Transmission speed	...	10 / 100 / 1000 Mbps, 5 LAN ports	...	...
Outputs	...	...	...	<ul style="list-style-type: none"> <li>• 4 pcs - Transistor outputs</li> <li>• 2 pcs - Relay outputs NO/NC</li> </ul>
MAC addresses table	...	2k	...	...
Mounting standard	...	...	VESA 100, 150, 200, 200x100, 300, 300x200, 400x200 400x300, 400	...
Screen size range	...	...	32 " ... 70 "	...
Communication	...	...	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS (Roger)</li> </ul>
Bearing capacity	...	...	75 kg	...
Events memory	...	...	...	Non-volatile log buffer of the last 250 000 events
Distance from mounting surface	...	...	47 mm	...
Color	Black	...	Black	...
Tilt adjustment	...	...	-10 ° ... 4 °	...
External dimensions	384 x 335 x 144 mm	...	...	...
Certificates	...	CE, FCC	...	...
Housing	...	Plastic, Desktop	...	...
Internal dimensions	365 x 245 x 110 mm	...	...	...
Output load	...	...	...	<ul style="list-style-type: none"> <li>• Transistor outputs : 1 A / 15 V DC</li> <li>• Relay outputs : REL1 - 1.5 A / 30 V DC REL2 - 5 A / 230 V AC</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• High-strength body,</li> <li>• Ergonomic handle,</li> <li>• Protective foam inside to protect tools,</li> <li>• Capacity : 10 kg,</li> <li>• 2 fasteners on the front to prevent accidental opening</li> </ul>	<ul style="list-style-type: none"> <li>• Protection against electrostatic discharge : - 8 kV (air-gap discharge) - 4 kV (contact discharge)</li> <li>• Protection against lightning discharges : 2 kV</li> <li>• Plug &amp; Play</li> </ul>	...	<ul style="list-style-type: none"> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Central management of the access control system,</li> <li>• Integration with the alarm system SATEL INTEGRA,</li> <li>• History of 250 000 events</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> <li>• DIN, TS-35 rail mounting</li> </ul>
Power supply	...	5 V DC / 1 A (power adapter included)	...	<ul style="list-style-type: none"> <li>• 24 V DC</li> <li>• 12 V DC</li> <li>• 18 V AC</li> </ul>
Battery backup support	...	...	...	✓
Operation temp	...	...	...	5 °C ... 40 °C
Permissible relative humidity	...	...	...	10 % ... 95 % (non-condensing)
Dimensions	...	87 x 52 x 24 mm	570 x 430 x 47 mm	105 x 85 x 50 mm
Weight	0.95 kg	0.046 kg	2 kg	0.12 kg
Manufacturer / Brand	...	DAHUA	...	ROGER
Guarantee	2 years	3 years	2 years	3 years