





	<a href="#">FLAT ELECTRIC CABLE YDYP-3X2.5</a>	<a href="#">ELECTRIC CABLE DY-2.5- BK/750V</a>	<a href="#">GROUNDING RESISTANCE METER UT-522 UNI-T</a>	<a href="#">MULTI-PURPOSE AGENT K2-07/250ML SPRAY 250 ml K2</a>
				
	1.60 EUR 1.60 EUR	0.43 EUR 0.43 EUR	197.93 EUR 197.93 EUR	3.24 EUR 3.24 EUR
Package	...	...	...	Spray 250 ml
In section	<b>100 m . Price for 1m when buying a whole roll</b>	<b>100 m . Price for 1m when buying a whole roll</b>	...	...
Inner conductor	3 x 2.5 mm <sup>2</sup> - Cu wire	2.5 mm <sup>2</sup> - Cu wire	...	...
Rated voltage	750 V	450 / 750 V	...	...
Outer coating	11.3 x 5.5 mm PVC	Ø 3.3 mm - PVC	...	...
Coating color	White	Black	...	...
Application	...	...	...	<ul style="list-style-type: none"> <li>• Elimination of squeaks,</li> <li>• Lubrication,</li> <li>• Removal of water,</li> <li>• Penetration,</li> <li>• Corrosion protection,</li> <li>• Surface preservation,</li> <li>• Removal of dirt</li> </ul>
Resistance measurement	...	...	40 Ω ± (2% + 20) @ 0.01 Ω , 400 Ω ± (2% + 3) @ 0.1 Ω , 4000 Ω ± (2% + 3) @ 1 Ω • Auxiliary resistance : 500 Ω ± 5 % • Measuring voltage : ≤ 10 V AC @ ~820 Hz	...
Ground voltage measurement	...	...	400 V ± (1.0% + 6) @ 1 V	...
Automatic change of measuring ranges	...	...	—	...
RS-232	...	...	—	...
USB	...	...	—	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Hold - stopping the meter reading,</li> <li>• The measurement can be performed in full or simplified configuration,</li> <li>• Warning of poor connection of leads during measurement,</li> <li>• Large, readable LCD display with backlight,</li> <li>• Low battery level alarm,</li> <li>• Aesthetic and solid construction,</li> <li>• The set includes a practical case</li> </ul>	<ul style="list-style-type: none"> <li>• Spray formulation with a straw for easy application in hard-to-reach places</li> <li>• Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places</li> <li>• It can be used in any position, even upside down</li> </ul>
Operation temp	...	...	5 °C ... 40 °C	...
Permissible relative humidity	...	...	≤ 80 % (non-condensing)	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	...	...	6 x 1.5V, type AA/LR6/FR6 battery - included	...
Weight	...	...	0.42 kg	0.23 kg
Dimensions	...	...	160 x 100 x 70 mm	Ø 52 x 199 mm
Manufacturer / Brand	...	...	UNI-T	K2
Guarantee	2 years	2 years	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00