





	<a href="#">3 PCS SET ACCESS POINT +ROUTER MAX18-3 Wi-Fi 6, 2.4 GHz, 5 GHz DAHUA</a>	<a href="#">ETHERNET + EPOE CONVERTER EOC-73</a>	<a href="#">TV OR MONITOR MOUNT BS-106S</a>	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-6G-SW/W (6 OUTLETS) 1.3 m</a>
				
	191.88 EUR 191.88 EUR	12.42 EUR 12.42 EUR	8.31 EUR 8.31 EUR	5.54 EUR 5.54 EUR
Mounting standard	...	...	VESA : 75, 100, 200, 400 x 200	...
Rated voltage	...	...	...	220 ... 240 V AC / 50 Hz
Total maximal current	...	...	...	10 A
Screen size range	...	...	23 " ... 42 "	...
In package	<b>3 pcs</b>	<b>2 pcs The price for package</b>	...	...
Maximal total load	...	...	...	2500 W
Bearing capacity	...	...	45 kg	...
Frequency range	2.4 GHz, 5 GHz	...	...	...
Distance from mounting surface	...	...	19 mm from wall	...
Transmission ports	...	1 pcs BNC	...	...
Number of outlets	...	...	...	6 grounded outlets 10A/250V CEE 7/5
Transmission speed	...	10 / 100 Mbps Half Duplex	...	...
Fuse	...	...	...	—
Tilt adjustment	...	...	—	...
Switch	...	...	...	✓
Horizontal rotation	...	...	—	...
Wire gauge	...	...	...	3 x 1.5 mm <sup>2</sup>
Rotation in the plane of the screen	...	...	—	...
Length of the cable	...	...	...	1.3 m
Antenna type	<ul style="list-style-type: none"> <li>• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in</li> <li>• 5 GHz : 2 x Omnidirectional antenna - built-in</li> </ul>	...	...	...
Housing	...	...	...	Plastic
Transmission range	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver	...	...
Color	...	...	Black	White

Standards	<ul style="list-style-type: none"> <li>• LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab,</li> <li>• Wi-Fi : IEEE 802.11 b/g/n/ac/ax</li> </ul>	...	...	...
Baud rates	574 Mbps + 1201 Mbps	...	...	...
Protections	WPA2	Short-circuit Protection against electrostatic discharge	...	...
LAN ports	3 x 10/100/1000 Mbps	1 pcs RJ45	...	...
Power supply	12 V DC / 1.5 A (power adapter included)	ePoE	...	...
Power consumption	≤ 12 W	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Support for Mesh technology,</li> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV</li> <li>• Easy and uniform management system for many devices - WiLynk application</li> <li>• Intuitive installation and configuration of many advanced functions</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• The device works only with recorders and cameras supporting the ePOE standard</li> <li>• Easy installation - doesn't require any configuration of IP nor MAC address</li> <li>• Length of the cable : 10.5 cm</li> </ul>	...	...
Operation temp	-10 °C ... 55 °C	...	...	...
Permissible relative humidity	5 % ... 95 %	...	...	...
Weight	0.23 kg	0.022 kg (single element)	1.45 kg	0.4 kg
Dimensions	95 x 95 x 73 mm	65 x 20 x 18 mm (single element)	455 x 260 x 19 mm	313 x 54 x 46 mm
Manufacturer / Brand	DAHUA	...	...	...
Guarantee	2 years	2 years	2 years	2 years