

	POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m	ELECTRIC CABLE YDY-5X2.5	OVERVOLTAGE LIMITER AXON-POWER/DIN
			
	43.10 NOK 43.10 NOK	30.21 NOK 30.21 NOK	414.19 NOK 414.19 NOK
Maximal voltage	250 V AC / 50 Hz
In section	...	100 m . Price for 1m when buying a whole roll	...
Total maximal current	10 A
Rated current	10 A
Maximal total load	2500 W
Number of outlets	4 grounded outlets 10A/250V CEE 7/5
Protection level Up L/PE, N/PE	≤ 1.3 kV
Fuse	—
Protection level Up L/N	≤ 3 kV
Inner conductor	...	5 x 2.5 mm ² - Cu wire	...
Switch	—
Rated voltage	220 ... 240 V AC / 50 Hz	450 / 750 V	230 V AC / 50 Hz
Wire gauge	3 x 1.5 mm ²
Nominal discharge current (L/N, L/PE, N/PE)	4 kA - 8/20 μs
Length of the cable	1.3 m
Outer coating	...	Ø 12 mm - PVC	...
Maximum stroke current (L/N, L/PE, N/PE)	10 kA 8/20 μs (type 2)
Coating color	...	White	...
Color	Black
Operation state indication	✓
Connectors type	2 x terminals
Housing	Plastic	...	• Plastic • DIN, TS-35 rail mounting
Weight	0.26 kg	...	0.075 kg
Dimensions	196 x 54 x 39 mm	...	86 x 58 x 35 mm
Guarantee	2 years	2 years	2 years