

	SWITCH POE GTX-A1-10-82-V2 8-PORT	PERFORATED MOUNTING RAIL A19-TS-35-C	INSULATION STRIPPER STRE/KLUCZ	LED LIGHTING CONTROLLER WL5 Wi-Fi, 2.4 GHz, RGB CCT (RGBWW) 12... 48 V DC MiBOXER / Mi-Light	ACCESS CONTROLLER ASC3202B DAHUA	ELECTRIC CABLE YKY-5X10.0
						
	52.47 EUR 52.47 EUR	13.74 EUR 13.74 EUR	9.66 EUR 9.66 EUR	15.85 EUR 15.85 EUR	505.49 EUR 505.49 EUR	8.81 EUR 8.81 EUR
Material	PET
Number of served transitions	2	...
Support	Cooperation with the access control systems	...
In section	100 m . Price for 1m when buying a whole roll
Material	...	Steel galvanized - DIN rail (TS-35) + Aluminum PA11
Application	Coaxial cable RG6 Coaxial cable RG59	Works with LED lighting - (RGB/RGBW/RGB CCT/CCT/MONO) 12-24V LED strips
Number of supported readers	• 2 pcs RS-485, • 2 pcs Wiegand	...
Battery backup support	—	...
Alarm inputs / outputs	2 / 2	...
Inner conductor	5 x 10.0 mm ² - Cu wire
LAN ports	• 8 x RJ45 10/100 Base-T (8 x PoE (802.3af/at)), • 2 x RJ45 10/100 Base-T - Uplink
Rated voltage	12 ... 48 VDC	...	0.6 / 1 kV
Management	—
Maximal total load	• 180 W @ 12 V, • 360 W @ 24 V
Outer coating	Ø 18.5 mm - PVC
Coating color	Black
LED diodes	Power, S - Extend, PoE, Link/Act
Total maximal current	6 A / Channel, 15 A (total)
Number of inputs	1
Number of outputs	5 (power)
Communication	• 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45)	...
Transmission speed	10 / 100 Mbps : 8 LAN & PoE ports + 2 Uplink ports
Maximal output power	30 W / port PoE 802.3af/at - 1 ... 8 ports
Maximal total power	96 W
Connector type	• screw terminals, • 5.5/2.1 socket / screw terminals - power input
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	...
Wireless	• Wi-Fi : IEEE 802.11 b/g/n, • 2.4 GHz
Radio communication range (at open area)	30 m
Operation modes	• N - Normal - the device operates as normal PoE switch • S - Extend - Range : 250 m @ 10 Mbps	• Main control mode • Sub control mode	...
Certificates	CE
Mobile phones support	• Android: Free application MiBoxer , • iOS (iPhone): Free application MiBoxer Access by a cloud (P2P) - Gateway required WL-BOX2 • The Tuya Smart free application on Android • The Tuya Smart free application on iOS

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	Perforated	...	<ul style="list-style-type: none"> The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control, Ability to work with any type of LED strip 	<ul style="list-style-type: none"> Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) 1000 indexed users Support up to 3000 finger prints Memory of 5000 RFID cards Support storage of 300 000 records 128 General Purpose Schedules Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above Tamper protections Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value Beep signal - Buzzer White list, Black list Web-Server built-in Software update via network Monitoring and configuration through network - SmartPSS Lite application Power output 12 V DC / 1 A - supplying power to the lock Support hardware I/O port configuration and export configuration diagrams ONVIF compliance 	...
Power supply	100 ... 265 V AC	<ul style="list-style-type: none"> 12 V DC / 2.5 A PoE (802.3at) 	...
Power consumption	<ul style="list-style-type: none"> ≤ 2 W (standby) max. 20.4 W @ 12 V (operation) max. 14.4 W @ PoE (operation) 	...
Housing	Desktop, Metal	Plastic	Plastic (PC + ABS)	...
Color	...	Silver + Black	...	White	White	...
IK rating	IK06	...
Operation temp	-10 °C ... 55 °C	-10 °C ... 40 °C	-10 °C ... 55 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
Weight	0.66 kg	0.38 kg	...	0.06 kg	0.72 kg	75.6 kg @ 100 m
Dimensions	207 x 105 x 32 mm	19 " x 1 U x 105 mm	...	124 x 37 x 22 mm	186 x 186 x 58 mm	...
Manufacturer / Brand	MiBOXER / Mi-Light	DAHUA	...
Guarantee	2 years	2 years	2 years	2 years	3 years	2 years