



	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-ST-9 ROGER</a>	<a href="#">LED LIGHTING CONTROLLER LED-W- WC/RF2 2.4 GHz, CCT 12 ... 24 V DC MiBOXER / Mi- Light</a>
		
	23653.96 CZK 23653.96 CZK	247.25 CZK 247.25 CZK
Number of served transitions	9 (two-way)	...
Number of supported readers	36	...
Application	...	Works with LED lighting - white LED strips with adjustable color temperature (CCT) 12-24V
Number of users	unlimited (purchase of the appropriate license required)	...
Rated voltage	...	12 ... 24 V DC
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Buffer memory	8 000 000 events buffer	...
Number of access zones	18	...
Number of alarm zones	18	...
Maximal total load	...	<ul style="list-style-type: none"> <li>• 144 W @ 12 V,</li> <li>• 288 W @ 24 V</li> </ul>
Total maximal current	...	12 A
Number of inputs	...	1
Battery backup support	12 V / 7 Ah	...
Number of outputs	...	2 (power)
Communication	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>	...
Connector type	...	<ul style="list-style-type: none"> <li>• screw terminals,</li> <li>• 5.5/2.1 socket / screw terminals - power input</li> </ul>
Wireless	...	2.4 GHz
Radio communication range (at open area)	...	30 m
Mobile phones support	...	—
Housing	...	Plastic
Color	...	White

Main features	<ul style="list-style-type: none"> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• The repeater function allows you to transfer control to subsequent LED-W-WC / LED-RGB-WC / LED-RGBW-WC modules even beyond the direct range of the remote control</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	...
Operation temp	5 °C ... 40 °C	-10 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.03 kg
Dimensions	175 x 72 x 30 mm	75 x 36 x 17 mm
Manufacturer / Brand	ROGER	MiBOXER / Mi-Light
Guarantee	3 years	2 years