




	EXPANSION PLUG KW-10/6X100 KLIMAS	IP CAMERA DS-2CD1067G2H-LIU(2.8MM) ColorVu - 6 Mpx Hikvision	LOCKABLE CASTOR A19-K*P2 TO RACK CABINET
			
	0.24 CHF 0.24 CHF	205.43 CHF 205.43 CHF	11.34 CHF 11.34 CHF
Standard	...	IP	...
In package	2 pcs The price for package
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Wheel diameter	70 mm
Drilling diameter	10 mm
Max cabinet's weight	250 kg
Expansion plug length	60 mm
Material	Metal / Plastic
Screw dimensions	Ø 6 x 100 mm, PZ-3
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Sensor	...	1/2.4 " Progressive Scan CMOS	...
Lens	...	2.8 mm	...
View angle	...	115 °	...
White light LED illuminator range	...	30 m	...
Range of IR illumination	...	30 m	...
Memory card slot	...	—	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network 	...
Main stream frame rate	...	20 fps @ 6 Mpx	...
Interface	...	10/100 Base-T (RJ-45)	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	6	...
ONVIF	...	—	...

Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles 	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	...	192.168.1.64	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	...	8000	...
Port ONVIF	...	80	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 550 mA 	...
Power consumption	...	<ul style="list-style-type: none"> • ≤ 8 W @ PoE • ≤ 6.6 W @ 12 V DC 	...
Housing	...	Compact, Metal	...
Color	...	White	...
"Index of Protection"	...	IP67	...
Mechanical protection class	...	—	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	...	0.3 kg	0.4 kg
Dimensions	...	Ø 70 x 173 mm	...
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	KLIMAS	Hikvision	...
SAP Code	...	311325494	...
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00