



	<a href="#">ROUTER ER-X EdgeMAX UBIQUITI</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-DMQ3803IR3-B - 8.3 Mpx, 4K UHD 3.3 ... 12 mm MOTOZOOM</a>
		
	65.57 EUR 65.57 EUR	174.09 EUR 174.09 EUR
Standards	IEEE 802.3ad, IEEE 802.1q	...
Processor	Dual-Core 880 MHz, MIPS1004Kc	...
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
LAN ports	5 x LAN 10/100/1000 Mbps (RJ-45)	...
Sensor	...	1/2.5 " SONY Starvis™ CMOS
WAN interface	configurable	...
Matrix size	...	8.3 Mpx
LED indicators	Power, LAN	...
DDNS	✓	...
DHCP server	✓	...
Protections	<ul style="list-style-type: none"> <li>• NAT network firewall</li> <li>• LAN ACL</li> <li>• Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV</li> </ul>	...
Management interface	<ul style="list-style-type: none"> <li>• Software EdgeOS, Software PC</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• IEEE 802.1Q VLAN</li> <li>• PPPoE</li> <li>• Static routing</li> <li>• DHCP</li> <li>• IPv6 compliance</li> <li>• IGMP</li> <li>• NAT</li> <li>• VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN</li> <li>• Dynamic DNS</li> <li>• Client - Radius support</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols</li> <li>• View topology and network status</li> <li>• RESET button</li> <li>• Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+": 4, 5 pins; "-": 7, 8 pins)</li> <li>• Possibility to mount to the wall</li> </ul>	...
Power supply PoE	Ubiquiti Passive PoE	...
Resolution	...	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps / 12.5 fps , 2704 x 1950 - 5 Mpx @ AHD / HD-CVI / HD-TVI, 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps , 1280 x 720 - 720p @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps
Range of IR illumination	...	40 m
IR illuminator power adjustment	...	Automatic
Operation temp	-10 °C ... 45 °C	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Lens	...	3.3 ... 12 mm Motozoom, AutoFocus

View angle	...	<ul style="list-style-type: none"> <li>• 90 ° ... 31 ° (manufacturer data)</li> <li>• 96 ° ... 32 ° (our tests result)</li> </ul>
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	—
OSD menu	...	✓
Main features	...	<ul style="list-style-type: none"> <li>• Motozoom lens, AutoFocus</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• AES - Auto Electronic Shutter</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 16</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 12 V DC / 0.5 A (power adapter included)</li> <li>• Passive PoE 24 V - port eth0/PoE IN</li> </ul>	12 V DC / 500 mA
Power consumption	max. 5 W	< 6 W
Housing	Metal	Dome, Metal
Color	...	White
"Index of Protection"	...	IP66
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.172 kg	0.52 kg
Dimensions	110 x 75 x 22 mm	Ø 119 x 104 mm
Supported languages	...	Polish, English
Manufacturer / Brand	UBIQUITI	BCS UNIVERSAL
Guarantee	2 years	3 years