

	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATTE	END CLAMP PV-KK/40-50/S FOR SOLAR PANELS 40 mm	ELECTRIC CABLE YKY-3X2.5
			
	668.60 DKK 668.60 DKK	3.03 DKK 3.03 DKK	10.26 DKK 10.26 DKK
Material	...	Aluminum	...
Height	...	40 mm	...
Hole diameter	...	9 mm	...
In section	100 m . Price for 1m when buying a whole roll
mounting screw	...	—	...
Inner conductor	3 x 2.5 mm ² - Cu wire
Rated voltage	0.6 / 1 kV
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
Color	...	Silver	...
Outer coating	Ø 10 mm - PVC
LAN ports	1 pcs RJ45 10 Mbps
Coating color	Black
Connectors description	<p>ETH10-2WIRE-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins) • Power • DATA - 2-wire <p>ETH10-2WIRE-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Passive PoE ("+"-": 4, 5 pins; "-": 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	10 Mbps
Transmission range	<ul style="list-style-type: none"> • 1000 m @ 2-wire • 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX • 100 m @ UTP : ETH10-2WIRE-RX - IP Camera

LED indicators	<ul style="list-style-type: none"> • Power • LAN • 2-wire
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH10-2WIRE-TX
Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers
Power supply	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : <ul style="list-style-type: none"> • 10 ... 56 V - Power The output PoE voltage is equal to the input voltage
Power consumption	1.35 W (total)
Housing	Plastic (PC)
"Index of Protection"	IP20
Operation temp	-25 °C ... 65 °C
Weight	0.03 kg (single element)	0.26 kg	...
Dimensions	51 x 51 x 24 mm (single element)	50 x 43 x 30 mm	...
Manufacturer / Brand	ATTE
Guarantee	3 years	2 years	2 years