

	<a href="#">IP CAMERA IPC-HFW2431T-ZS-27135 - 4.0 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA</a>	<a href="#">ENCLOSURE LOCK TPR-ZAM</a>
		
	2788.89 SEK 2788.89 SEK	45.14 SEK 45.14 SEK
Standard	TCP/IP	...
Application	...	TPR enclosures
Sensor	1/3 " Progressive Scan CMOS	...
Thread type	...	M16
Matrix size	4.0 Mpx	...
Bolt length	...	28 mm
Distance of the bolt from the lock	...	11.5 mm
Main features	...	2 keys included
Material	...	Nickel
Resolution	2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	2.7 ... 13.5 mm - Motozoom	...
View angle	<ul style="list-style-type: none"> <li>• 104 ° ... 28 ° (manufacturer data)</li> <li>• 106 ° ... 27 ° (our tests result)</li> </ul>	...
Compression	H.265 / H.264 / MJPEG	...
S/N ratio	> 50 dB	...
Range of IR illumination	60 m	...
Alarm inputs / outputs	—	...
Bitrate	<ul style="list-style-type: none"> <li>• 12 ... 8448 kbps - H.265</li> <li>• 24 ... 10240 kbps - H.264</li> </ul>	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps - 4.0 Mpx</li> <li>• 25 fps - 3.7 Mpx</li> </ul>	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, SNMP, QoS, UPnP, NTP, Multicast, Bonjour	...
Audio	—	...
WEB Server	Built-in, NVR compliance	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Max. number of on-line users	20	...
ONVIF	16.12	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.108	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
RS-485 interface	—	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 4</li> <li>• Auto White Balance</li> <li>• IVS analysis : crossing the line (tripwire), intrusion</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 1170 mA</li> </ul>	...
Power consumption	< 14 W	...
Housing	Compact, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Supported languages	English, Polish	...
Weight	0.85 kg	0.022 kg
Dimensions	244 x 79 x 76 mm	39 x 20 x 22 mm
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00