



| | | |
|-----------------------------------|---|---|
| | CONNECTOR FOR LED STRIPS UQS-COB-8W-CS 8 mm | IP CAMERA DS-2CD2T87G2H-LI(2.8MM)(EF) ColorVu - 8.3 Mpx, 4K UHD Hikvision |
| |  |  |
| | 1.29 AUD 1.29 AUD | 1112.20 AUD 1112.20 AUD |
| Standard | ... | TCP/IP |
| Application | Works with LED lighting - COB LED strips | ... |
| Sensor | ... | 1/1.8 " Progressive Scan CMOS |
| Strip width | 8 mm | ... |
| Matrix size | ... | 8.3 Mpx |
| Length of the cable | 140 mm | ... |
| Resolution | ... | 3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.8 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p |
| Lens | ... | 2.8 mm |
| View angle | ... | <ul style="list-style-type: none"> • 105 ° (manufacturer data) • 100 ° (our tests result) |
| White light LED illuminator range | ... | 60 m |
| Range of IR illumination | ... | 60 m |
| Memory card slot | ... | Micro SD memory cards up to 512GB support (possible local recording) |
| Image compression method | ... | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Alarm inputs / outputs | ... | — |
| Audio | ... | — |
| Main stream frame rate | ... | 25 fps @ 8.3 Mpx |
| Network interface | ... | 10/100 Base-T (RJ-45) |
| WEB Server | ... | Built-in |
| Max. number of on-line users | ... | 6 |
| ONVIF | ... | ✓ |

| | | |
|-------------------------------|-------------|--|
| Main features | ... | <ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection |
| Mobile phones support | ... | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect |
| Default IP address | ... | 192.168.1.64 |
| Default admin user / password | ... | admin / - The administrator password should be set at the first start |
| Web browser access ports | ... | 80 |
| PC client access ports | ... | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports | ... | 8000 |
| Port ONVIF | ... | 80 |
| RTSP URL | ... | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ |
| Power supply | ... | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 710 mA |
| Power consumption | ... | <ul style="list-style-type: none"> • ≤ 9.5 W @ PoE • ≤ 8.5 W @ 12 V DC |
| Housing | Plastic | Compact, Metal |
| Color | Transparent | White |
| "Index of Protection" | — | IP67 |

| | | |
|----------------------|----------------|--|
| Vandal-proof | ... | — |
| Operation temp | ... | -30 °C ... 60 °C |
| Weight | 0.002 kg | 1.14 kg |
| Dimensions | 12 x 10 x 5 mm | 287 x 93 x 91 mm |
| Supported languages | ... | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Manufacturer / Brand | MW Lighting | Hikvision |
| SAP Code | ... | 311323654 |
| Guarantee | 2 years | 3 years |