






	RACK CABINET LOCK A19-LOCK-N	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-B2A21-0360B -1080p 3.6 mm DAHUA	PHOTOCELL FAAC-XP20D TXRX SET	SILICONE CAMERA COVER FRS10-B-IMOU	CRIMP PLUG BNC-W/ZAC-RG58
					
	1.89 EUR 1.89 EUR	51.89 EUR 51.89 EUR	78.44 EUR 78.44 EUR	8.28 EUR 8.28 EUR	0.70 EUR 0.70 EUR
Application	EPRADO BLUE
Thread type	M18
Connector type	BNC Straight plug
Bolt length	26 mm
Attachment of connector elements	Crimping
Distance of the bolt from the lock	16 mm
Standard	...	AHD, HD-CVI, HD-TVI, PAL
Shield fastening	Crimping
Wire mounting	Crimping
Sensor	...	1/2.7 " Progressive Scan CMOS
Beam width	± 7 ° @ 20 m , ± 13.5 ° @ 5 m
Application	Coaxial cable
Matrix size	...	2.1 Mpx
Material	Zinc alloy	Silicon	...
Operation range	20 m
Cable diameter	max. 5.0 mm
Impedance	50 Ω
Response time	13 ms
Material	Metal
Example of application	• RG58
Current consumption	• 20 mA Transmitter • 30 mA Receiver
Number of relay outputs	1
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Relay maximal load	max. 60 VA / 24 W
Lens	...	3.6 mm
Output	1 x NC
View angle	...	• 93 ° (manufacturer data) • 90 ° (our tests result)
Range of IR illumination	...	20 m
Main features	2 keys included	...	• Cooperation with the FAAC gate automation system • Angle adjustment range ± 90 ° horizontal • Surface/column mounting • Immunity to environmental changes	...	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C
IR illuminator power adjustment	...	Automatic
Operation temp	-20 °C ... 55 °C
Video output	...	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
OSD menu	...	OSD menu available via DAHUA recorder

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Auto White Balance
Power supply	...	12 V DC / 220 mA	24 V AC/DC
Power consumption	...	≤ 2.7 W
Housing	...	Compact, Aluminum	Plastic
Color	...	White	Black	Black	...
"Index of Protection"	...	IP67	IP54
Operation temp	...	-40 °C ... 60 °C
Weight	0.04 kg	0.25 kg	<ul style="list-style-type: none"> • 0.070 kg Transmitter • 0.076 Receiver 	0.03 kg	0.010 kg
Dimensions	47 x 28 x 23 mm	158 x 70 x 70 mm	130 x 42 x 41 mm Transmitter / Receiver	65 x 78 x 76 mm	Ø 14 mm x 30 mm
Manufacturer / Brand	EPRADO	DAHUA	FAAC	DAHUA	...
Guarantee	2 years	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00