

	LIGHTNING PROTECTION SYSTEM CLAMP JK-50/2	KEYSTONE CONNECTOR FX-RJ11/12	NVR NVR304-32X 32 CHANNELS UNIVIEW
			
	5.39 GBP 5.39 GBP	0.74 GBP 0.74 GBP	1372.80 GBP 1372.80 GBP
Application	Mast
Standard	TCP/IP
Connector type	...	Socket RJ11, RJ12	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px
Color	...	White	...
Wire mounting	...	KRONE quick-connector	...
Video outputs	2 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Application	...	Patch panel Keystone	...
Impedance	...	100 Ω	...
Material	Metal	PET	...
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	1 pcs CINCH
Audio outputs	1 pcs CINCH
Main features	<ul style="list-style-type: none"> • Mast diameter max. Ø 50 mm • Allows to mount the lightning conductor to the mast, mounting element - Clamp, • The whole galvanized 	<ul style="list-style-type: none"> • Very easy and quick installation without any tools • Corrosion resistance • Keystone assembly standard 	...
Image compression method	Ultra 265 / H.265 / H.264
Bitrate	max. 384 Mbps
Supported hard drives	4 x 10 TB SATA + 1 x eSATA Possibility of operation the disks in RAID 1/5 array
Recording modes	Manual, Sensor, Motion detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)

Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9/16/25/36 channel synchronous playback
Network interface	2 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
ONVIF	✓
Default IP address	DHCP or 192.168.1.30
Default admin user / password	admin / 123456
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	2 x USB 2.0 1 x USB 3.0
Serial ports	RS-485, RS-232
Alarm inputs / outputs	16 / 4
PTZ control	• PTZ Uniview cameras • RS-485 - PELCO-D/P and others
Motion Detection	✓
Intelligent image analysis	✓



Main features	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, people counting, crowd gathering estimation, scene changing, objects tracking • Smoke and temperature detection, fire detection • Audio detection • Motion detection with human/vehicle silhouette recognition • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Fisheye-Dewarping - correction of the "fish eye" view to the perspective view • VIDEO signal loss alarm • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its
Mouse support	✓
IR remote controller in the set	—
Switch PoE	—
Power supply	100 ... 240 V AC
Power consumption	max. 25 W (without HDD)
Operation temp	-10 °C ... 55 °C
Weight	0.39 kg	0.006 kg	5.2 kg
Dimensions	175 x 60 x 30 mm	20 x 23 x 27 mm (W x H x D)	442 x 426 x 89 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	UNIVIEW
Guarantee	2 years	2 years	3 years

