



	SWITCH POE CS4218-16ET-240 16-PORT SFP DAHUA	REAR SUPPORT FOR THE MOUNTING PROFILE USP-TN-600 FOR SOLAR PANELS
		
	6657.68 SEK 6657.68 SEK	72.78 SEK 72.78 SEK
Material	...	Aluminum
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 10/100 Base-T (2 x Hi-PoE (802.3bt) + 14 x PoE (802.3af/at)), • 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink 	...
Management	✓	...
LED diodes	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 16 LAN & PoE ports, • 10 / 100 / 1000 : 2 RJ45 (Uplink) ports, • 1000 : 2 SFP (Uplink) ports 	...
Maximal output power	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 16 ports 	...
Maximal total power	240 W	...
MAC addresses table	8k	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 	...

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Can be mounted in a Rack 19" cabinet 	...
Certificates	CE	...
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Housing	Metal	...
Power supply	100 ... 240 V AC @ 47 ... 63 Hz	...
Power consumption	max. 265 W	...
Operation temp	-10 °C ... 55 °C	...
Weight	2.29 kg	0.32 kg
Dimensions	440 x 220 x 44 mm, RACK 19", 1U	600 x 35 x 35 mm
Manufacturer / Brand	DAHUA	...
Guarantee	5 years	2 years