




	CABLE GLAND D/M-16X1.5 IP68 M16 x 1.5	IP VANDALPROOF CAMERA BCS-L-DIP22FC-AI2 NightColor - 1080p 3.6 mm	GREASE WITH MOLYBDENUM DISULFIDE GREASE-MOS2/400 SPRAY 400 ml AG TERMOPASTY
			
	0.33 EUR 0.33 EUR	141.79 EUR 141.79 EUR	6.57 EUR 6.57 EUR
Standard	...	TCP/IP	...
Package	Spray 400 ml
Sensor	...	1/2.8 " Progressive Scan CMOS	...
Type (size)	M16 x 1.5
Matrix size	...	2 Mpx	...
Application	Lubrication, Protection against moisture ingress
Cable diameter	Ø 4 ... 8 mm
Main features	Spray formulation with a straw for easy application in hard-to-reach places
Material	Plastic
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	...	3.6 mm	...
View angle	...	• 88 ° (manufacturer data) • 83 ° (our tests result)	...
RS-485 interface	...	—	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	1 / 1	...
Audio	...	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	...
Main stream frame rate	...	25 fps @ 1080p	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, IEEE 802.1x, SNMP	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	20	...
ONVIF	...	20.06	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Heat map - the selection in the image by corresponding colors the areas with different traffic • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, abandoned/missing object, fast moving, loitering detection, scene changing, illegal parking, detection of people gathering, people counting - detection and maintenance of 4 independent areas, face detection - advanced face recognition and search functions 	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Default IP address	...	192.168.1.108	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Power supply	...	• PoE (802.3af), • ePoE, • 12 V DC / 320 mA	...
Power consumption	...	≤ 3.8 W	...
Housing	...	Dome - Metal	...
Color	...	White	...
"Index of Protection"	IP68	IP67	...
Vandal-proof	...	IK10	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	0.006 kg	0.46 kg	0.38 kg
Dimensions	31 x 24 x 24 mm	Ø 122 x 90 mm	Ø 65 x 200 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	...	BCS	AG TERMOPASTY
Guarantee	...	3 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00