





	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D0T-IRF(2.8mm)(C) - 1080p Hikvision</a>	<a href="#">REMOTE CONTROL FOR LED LIGHTING CONTROLLERS LED-CONTROL-W/RF 2.4 GHz, MONO, CCT MiBOXER / Mi-Light</a>	<a href="#">INFRA-RED BARRIERS AN900-15 1 BEAM</a>	<a href="#">EXPANSION PLUG KS-14/10X100 KLIMAS</a>
				
	44.93 GBP 44.93 GBP	6.48 GBP 6.48 GBP	10.38 GBP 10.38 GBP	0.55 GBP 0.55 GBP
Number of beams	...	...	1	...
Detection method	...	...	1 beam blocked	...
Outdoor detection range	...	...	3 ... 15 m	...
Material	...	...	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>
Standard	AHD / HD-CVI / HD-TVI / PAL	...	...	...
Number of channels	...	4	...	...
Drilling diameter	...	...	...	14 mm
Sensor	Progressive Scan CMOS	...	...	...
Indoor detection range	...	...	3 ... 20 m	...
Wireless	...	2.4 GHz	...	...
Expansion plug length	...	...	...	80 mm
Matrix size	2.1 Mpx	...	...	...
Radio communication range (at open area)	...	30 m	...	...
Beam characteristics	...	...	940 nm - Modulated Infra-Red stream	...
Main features	...	Large, readable buttons	...	...
Screw dimensions	...	...	...	Ø 10 x 100 mm, SW-17
Alarm period	...	...	≥ 0.1 s	...
Tamper contact	...	...	—	...
Application	...	Works with LED lighting : single-color (MONO) 12-24V LED strips, white LED strips with adjustable color temperature (CCT) 12-24V	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> <li>• Natural stone</li> </ul>
Angles adjustment range	...	...	—	...
Resolution	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 @ PAL	...	...	...
Assembly	...	...	on the wall or pole	...
Lens	2.8 mm	...	...	...
Operation temp	...	-20 °C ... 60 °C	...	...
View angle	<ul style="list-style-type: none"> <li>• 106 ° (manufacturer data)</li> <li>• 100 ° (our tests result)</li> </ul>	...	...	...
Range of IR illumination	25 m	...	...	...
IR illuminator power adjustment	Automatic	...	...	...

Current consumption	...	...	20 mA - Transmitter , 18 mA - Receiver	...
Alarm output	...	...	Relay (AC/DC 36V max. 1A)	...
Video output	1 Vpp / 75 $\Omega$ - AHD / HD-CVI / HD-TVI / PAL, BNC socket	...	...	...
OSD menu	✓	...	...	...
Operation temp. / Relative humidity	...	...	-25 °C ... 55 °C / max. 95 %	...
Transmitter or receiver dimensions	...	...	49 x 76 x 22 mm	...
Transmitter and receiver weight	...	...	0.036 kg	...
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• IR illuminator optimization</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Day/night mode</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...	...
Power supply	12 V DC / 250 mA	2 x 1.5V, type AAA/LR03 battery (not included)	9 V ... 16 V DC / AC - selectable by switch	...
Power consumption	$\leq$ 3 W	...	...	...
Housing	Compact, Metal	Plastic	...	...
Color	White	White	...	...
"Index of Protection"	IP67	...	IP66	...
Operation temp	-40 °C ... 60 °C	...	...	...
Weight	0.26 kg	0.044 kg (without battery)	...	...
Dimensions	$\varnothing$ 70 x 138 mm	110 x 53 x 21 mm	...	...
Supported languages	Polish, English	...	...	...
Manufacturer / Brand	Hikvision	MiBOXER / Mi-Light	...	KLIMAS
SAP Code	300511939	...	...	...
Guarantee	3 years	2 years	2 years	2 years